

STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 72472 (20169)
Permit No. _____
Basin No. 207

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 72472
WELL NAME (if applicable): _____

1. OWNER/CLIENT NAME Tiber Bozgary/Bright Sky Energy DETAILED ADDRESS AT WELL LOCATION Murphy Meadows
MAILING ADDRESS 17501 Rim Rock Drive
Golden, CO 80401
Subdivision Name: NA County: Nye

2. PLS LOCATION SW 1/4 SW 1/4 35 Sec 8 T15S 61 E Latitude 38° 30' 08" UTM E NAD 27
PERMIT/WAIVER NO. OG 296 113-651-01 Longitude 115° 05' 38" UTM N NAD 83/WGS 84
Issued by Water Resources Current Parcel No.

3. WORKED PERFORMED
 New Well Deepen: Orig WL# _____
 Replacement: Original well log # _____
 Recondition: Original well log # _____
4. PROPOSED USE
 Domestic Irrigation Monitor Auger Rotary RVC
 Mining / Dewater Com / Ind Stock Air Mud Sonic
 Test / Other Mun / QM Rec Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thickness
Sand/Rock			0	10	10
Brown/clay/Rock			10	15	5
gray clay/rock			15	18	3
Fine gravel		✓	18	22	4
Brown clay/rock			22	33	11
Fine gravel		✓	33	34	1
Brown clay/rock			34	70	36
Fine gravel		✓	70	72	2
Brown clay/rock		✓	72	87	15
Fine gravel		✓	87	91	4
Brown clay/rock			91	94	3
Fine gravel		✓	94	98	4
Brown clay/rock			98	103	5
Fine gravel		✓	103	105	2
Brown clay/rock			105	114	9
Fine gravel		✓	114	116	2
Brown clay/sand			116	177	61
Fine gravel		✓	177	180	3
Brown clay/sand			180	183	3
Fine gravel		✓	183	200	17

Nad 27
38.50222° N
115.093869° W

9. WELL CONSTRUCTION
Depth Drilled: 200 Feet Depth Cased: 200 Feet
HOLE DIAMETER (BIT SIZE)
From 13 1/2 Inches To 200 Feet
Inches Feet
Inches Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
<u>8 5/8</u>	<u>16.96</u>	<u>.188</u>	<u>0</u>	<u>20</u>
<u>8 5/8</u>	<u>8.38</u>	<u>PVC SDR 17</u>	<u>20</u>	<u>200</u>

PERFORATIONS:
Type of perforation: factory saw
Size of perforation: .032"
From 60 Feet To 120 Feet
From 160 Feet To 200 Feet

ANNULAR MATERIALS
 Sanitary Seal 0 to 50
 Neat Cement 0 to 45 Pumped Poured
 Cement Grout to Pumped Poured
 Concrete Grout to Pumped Poured
 Bentonite Chips 45 to 50 Pumped Poured
 Bentonite Grout to Pumped Poured
 15% 20% Other, explain: _____
 Gravel Pack [> 0.2 in.] 50 to 200 Pumped Poured
 Sand Pack [< 0.2 in.] to Pumped Poured
 Other, explain: _____

Date started: 07/02/2015
Date completed: 07/05/2015

7. WATER QUALITIES
Static water level: 10 Feet below land surface
Artesian Flow: _____ G.P.M. _____ P.S.I.
Water Temperature: 54 ° Fahrenheit
Water Quality: Ph 8.6 TDS 147

8. WELL TEST DATA

Test Method:	G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
<input type="checkbox"/> Bailor			
<input checked="" type="checkbox"/> Pump			
<input checked="" type="checkbox"/> Air Lift			
air lift	<u>350</u>	<u>3</u>	<u>3</u>
pump	<u>120</u>	<u>3</u>	<u>6</u>

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name David Gibson Contractor
Address P.O. Box 203 Lund, NV 89517
Nevada contractor's license number as issued by the State Contractor's Board: 0077887
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 2579
Signed: Franton Gibson
Date: 07/12/2015