STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 122698
Permit No. 84707T
Basin No. 083

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO 71617
WELL NAME (if applicable):

1. OWNER/CLIENT NAME Roger Norman
MAILING ADDRESS P.O. Box 838
Poway, CA 92074

DETAILED ADDRESS AT WELL LOCATION 145 Britain Ct.
Subdivision Name: County: Storey

2. PLS LOCATION NE ¼ NW ¼ 32 Sec 20 N/S 22 E
PERMIT/WAIVER NO. 84707T (Issued by Water Resources) 005-031-08 (Current Parcel No.)

Latitude 39.5615 UTM E ☐ NAD 27
Longitude 119.5063 UTM N ■ NAD 83/WGS 84

3. WORKED PERFORMED
■ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ■ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ■ Rotary ☐ RVC
☐ Air ■ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Sand			0	5
Sand, brown clay			5	10
Brown clay, gravel			10	15
Gravel, sand			15	85
Red volcanic rock			85	98
Waiver R-849				
Nad 27				
39.561588°N				
119.505288°W				

Date started 27-May 20 15
Date completed 15-Jun 20 15

9. INSTRUCTION
Depth Drilled: 98 Feet Depth Cased: 96 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
15	Inches	0	Feet	98	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
10 3/4	28.04	.250	+2	96

ANNULAR MATERIALS

Sanitary Seal ■ Yes ☐ No

☐ Neat Cement		to		☐ Pumped	☐ Poured
■ Cement Grout	0	to	30	■ Pumped	☐ Poured
☐ Concrete Grout		to		☐ Pumped	☐ Poured
☐ Bentonite Chips		to		☐ Pumped	☐ Poured
■ Gravel Pack [> 0.2 in.]	30	to	96	☐ Pumped	■ Poured
☐ Sand Pack [< 0.2 in.]		to		☐ Pumped	☐ Poured
☐ Other, explain:		to		☐ Pumped	☐ Poured

PERFORATIONS

Type of perforation: Louvered Full Flow .07 Slot
Size of perforation: Louvered .07 Slot

From	36	Feet	To 96	Feet
From		Feet	To	Feet
From		Feet	To	Feet
From		Feet	To	Feet
From		Feet	To	Feet

7. WATER QUALITIES
Static water level: 11 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: 70 ° Fahrenheit
Water Quality: Clear

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ■ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
	300+		3.5
Pump	700	26.5	19 hrs

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.

Name A.S.A.P. Pump & Well Service, LLC. (Contractor)
Address P.O. Box 60130 Reno, Nevada 89506 (Contractor)

Nevada contractor's license number as issued by the State Contractor's Board 35387C
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller) 2362

Signed Larry Welch
(Signature of licensed contractor, on-site or contractor)
Date 7-2-15

RECEIVED 2015 JUL 15 AM 11:15 STATE ENGINEERS OFFICE

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. 1 of pg. 1