STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 122746
Permit No. 84417T
Basin No. 187

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 72708
WELL NAME *(If applicable)*:

1. OWNER/CLIENT NAME Newmont Mining Corp. LCW-000005
MAILING ADDRESS 1655 Mountain City Hwy.
Elko, NV. 89801

DETAILED ADDRESS AT WELL LOCATION Long Canyon Site,
West of Wendover, NV.
Subdivision Name: *County:* Elko

2. PLS LOCATION NW ¼ NE ¼ 15 Sec 36 (N)S 66 E
PERMIT/WAIVER NO. 84417T
Issued by Water Resources *Current Parcel No.*

Latitude UTM E 710843 [X] NAD 27
Longitude UTM N 4542637 [ ] NAD 83/WGS 84

3. WORKED PERFORMED
[X] New Well [ ] Deepen: Orig WL#
[ ] Replacement: Original well log #
[ ] Recondition: Original well log #

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Monitor
[X] Mining / Dewater [ ] Com / Ind [ ] Stock
[ ] Test / Other [ ] Mun / QM [ ] Rec

5. WELL TYPE
[ ] Auger [ ] Rotary [ ] RVC
[ ] Air [ ] Mud [ ] Sonic
X Other Flooded Rev.

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Grey tan & white rock			0	95
Dk gry, brn, tan rock w/clay			95	120
Dk & lt. grey rock w/clay			120	170
Dk gry, brn, tan rock w/little clay			170	320
Lt. gry & tan rock w/clay			320	325
Gry, tan & brn rock			325	355
Gry rock w/brn clay			355	360
Lt. & dk. gry rock			360	400
Lt. gry & tan rock			400	425
Lt. gry & tan rock w/little clay			425	520
Tan rock w/clay			520	565
Lt. & dk. gry rock			565	610
Tan & gry rock w/clay			610	620
Material used:				
150 X 94# Cement bags			5	60
124 X 94# Cement bags			5	100
18 X 50# 3/8" Holeplug			100	110
18 X 2800# 1/4" X3/8" Gravel s/s			110	620
NAD27				
41.009583°N				
114.492813°W				

Date started: 19-May , 20 15
Date completed: 2-Jun , 20 15

9. CONSTRUCTION
Depth Drilled: Feet 620 Depth Cased: 618 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
31	Inches	0	Feet	60	Feet
19	Inches	60	Feet	620	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
22	33.68	.375	0	60
12.750	86.61	.250	+2	618

ANNULAR MATERIALS
Sanitary Seal X Yes [ ] No

X Neat Cement	5	to 100	[ ] Pumped	X Poured
[ ] Cement Grout		to	[ ] Pumped	[ ] Poured
[ ] Concrete Grout		to	[ ] Pumped	[ ] Poured
X Bentonite Chips	100	to 110	[ ] Pumped	X Poured
X Gravel Pack [> 0.2 in.]	110	to 620	X Pumped	[ ] Poured
[ ] Sand Pack [< 0.2 in.]		to	[ ] Pumped	[ ] Poured
X Other, explain: Neat Cement Plug	610	to 620	X Pumped	[ ] Poured

PERFORATIONS:
Type of perforation: Louvered
Size of perforation: 0.125

From	Feet	To	Feet
218	Feet	598	Feet
	Feet		Feet
	Feet		Feet
	Feet		Feet
	Feet		Feet

7. WATER QUALITIES
Static water level: 156 Feet below land surface
Artesian Flow: N/A G.P.M. N/A P.S.I.
Water Temperature: 75 ° Fahrenheit
Water Quality: Good/Clear

8. WELL TEST DATA
Test Method: [ ] Bailer [ ] Pump X Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
380	N/A	1

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Boart Longyear
Contractor
Address 2745 California Ave., SLC., UT. 84104
Contractor
Nevada contractor's license number as issued by the *State Contractor's Board:* 0021976
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller):* 2452
Signed:
By driller performing actual drilling on site or contractor
Date: 1-Jul-15

RECEIVED 2015 JUL -6 AM 11:41 DIV. OF WATER RESOURCES ENGINEERS OFFICE

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. 1 of pg. 1