STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 122824
Permit No.
Basin No. 101

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 72904
WELL NAME *(If applicable)*:

1. OWNER/CLIENT NAME Kasm Construction
MAILING ADDRESS 782 Divot Dr
Fernley, NV 89408

DETAILED ADDRESS AT WELL LOCATION 1425 Skyridge Ln
Fallon, NV 89406
Subdivision Name: *County:* Churchill

2. PLS LOCATION SE ¼ NW ¼ 20 Sec 19 N/S 28 E
PERMIT/WAIVER NO. 008-177-72
Issued by Water Resources *Current Parcel No.*

Latitude 39.49725 UTM E ☐ NAD 27
Longitude -118.87016 UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☒ Rotary ☐ RVC
☐ Air ☒ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Top Soil			0	13
Brown Clay			13	31
Brown Gravel			31	60
Gray Clay/Sand			60	72
Gray Gravel			72	81
Green Gravel			81	92
Brown Gravel		X	92	105

NAD 27
39.497334°N
118.869171°W

Date started: 25-Jun , 20 15
Date completed: 26-Jun , 20 15

7. *WATER QUALITIES*
Static water level: 30 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: cool ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
		1

9. *INSTRUCTION*
Depth Drilled: 105 Feet Depth Cased: 105 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
12	Inches	0	Feet	105	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.92	.188	+2	10
6	4	.316	10	105

ANNULAR MATERIALS
Sanitary Seal ☒ Yes ☐ No

☒ Neat Cement	0	to 100	☒ Pumped	☐ Poured
☐ Cement Grout		to	☐ Pumped	☐ Poured
☐ Concrete Grout		to	☐ Pumped	☐ Poured
☐ Bentonite Chips		to	☐ Pumped	☐ Poured
☒ Gravel Pack [> 0.2 in.]	100	to 105	☐ Pumped	☒ Poured
☐ Sand Pack [< 0.2 in.]		to	☐ Pumped	☐ Poured
☐ Other, explain:		to	☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: Saw Cut
Size of perforation: 1/8.
From 102 Feet To 105 Feet
From Feet To Feet
From Feet To Feet
From Feet To Feet
From Feet To Feet

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Parsons Drilling, Inc. Contractor
Address P.O. Box 1265 Fallon, NV 89406 Contractor
Nevada contractor's license number as issued by the *State Contractor's Board:* 29064
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller):* 2509
Signed: *By driller performing actual drilling on site or contractor*
Date: 6/29/2015

RECEIVED JUL 2 2015 NEVADA DIVISION OF WATER RESOURCES

(Rev 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.