STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 172864
Permit No.
Basin No. 179

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 72718
WELL NAME *(If applicable)*: P-3

1. OWNER/CLIENT NAME Robinson Nevada mining company
MAILING ADDRESS 4232West White Pine County Rd44
Ruth Nevada 98319 SW

DETAILED ADDRESS AT WELL LOCATION
Robinson Mine Ruth NV
Subdivision Name: *County:* White Pine

2. PLS LOCATION ~~NW~~ ¼ ~~NE~~ SE ¼ 18 Sec 16N N/S 62 E
PERMIT/WAIVER NO. M/O-1994
Issued by Water Resources *Current Parcel No.*

Latitude UTM E 669009 ☐ NAD 27
Longitude UTM N 4347983 ■ NAD 83/WGS 84

3. WORKED PERFORMED
■ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ■ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☐ Rotary ■ RVC
■ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Dump			0	55
Gray-tan limestone			55	985
Gray-tan limestone	X		985	1225
Gray-tan limestone		X	1175	1225

NAD27
39.264724°N
115.040965°W

Date started: June 25 , 20 15
Date completed: July 11 , 20 15

9. INSTRUCTION
Depth Drilled: 1225 Feet Depth Cased: 1217 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
13-1/4	Inches	0 Feet	45 Feet
8.5	Inches	45 Feet	1225 Feet
	Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
12-3/4		0.250	45	+3
4-1/2		0.250	1217	+2

ANNULAR MATERIALS
Sanitary Seal ■ Yes ☐ No

■ Neat Cement	20	to 0	☐ Pumped	■ Poured
☐ Cement Grout		to	☐ Pumped	☐ Poured
☐ Concrete Grout		to	☐ Pumped	☐ Poured
■ Bentonite Chips	1169	to 20	☐ Pumped	■ Poured
☐ Gravel Pack [> 0.2 in.]		to	☐ Pumped	☐ Poured
■ Sand Pack [< 0.2 in.]	1225	to 1169	■ Pumped	☐ Poured
☐ Other, explain:		to	☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: Mill Slot
Size of perforation: 0.035
From ~~1179~~ 1177 Feet To 1177 Feet
From Feet To Feet
From Feet To Feet
From Feet To Feet
From Feet To Feet

7. WATER QUALITIES
Static water level: 1175 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: 58 ° Fahrenheit
Water Quality: Good

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ■ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
1-1/4 pipe	1/4		1

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Boart Longyear Company
Contractor
Address PO Box 2748 Elko, NV. 89803
Contractor

Nevada contractor's license number as issued by the *State Contractor's Board:* 0021976
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller):* 2446
Signed: Byron Baty
By driller performing actual drilling on site or contractor
Date: 07/27/15

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.

Corrected log 2/3/16