STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 128013
Permit No.
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36847

1. OWNER C.C. Public Works
MAILING ADDRESS 500 S. Grand Central Pkwy
Las Vegas, NV. 89155-0000

ADDRESS AT WELL LOCATION None Public Right-of-Way
Subdivision Name: Well 24 County: Clark

2. LOCATION SE ¼ NE ¼ Sec 29 T 21 N R 62 E
PERMIT/WAIVER No. MO-3019 (Issued by Water Resources) 161-29-699-008 (Parcel No.)

Latitude 36°5'42.38" UTM E ☐ NAD 27
Longitude -115°03'50.42" N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC
☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
FILL A Cover Aggibase		0	2	2
SILTY SAND		2	7	5
SILTY CLAY		7	10½	3½
SAND W/SILT	Wet	10½	15	4½
SILTY CLAY		15	35	20

DCNR/DWR/SNBC
RECEIVED
MAR 17 2015

Date started: 2/10, 20 15
Date completed: 2/10, 20 15

7. Water Level
Static water level: 11' 3" feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality:

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

9. WELL CONSTRUCTION
Depth Drilled Feet Depth Cased Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
6½	Inches	0	Feet	35	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2" sch 40 PVC		AstM F480	0	35

Perforations:
Type of perforation Factory Slots
Size of perforation .020
From 10 feet to 35 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☒ Concrete Grout 0 to 6 ☐ Pumped ☒ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 8 to 35 ☐ Pumped ☒ Poured
Type: #12 Silica Sand
Bentonite Chips: ☒ Yes ☐ No 6 to 8 ☐ Pumped ☒ Poured
Type: 3/8 Bentonite Hole Plug

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Elite Drilling Inc. (Contractor)
Address 4255 W Post Rd Las Vegas, NV 89118 (Contractor)

Nevada contractor's license number issued by the State Contractor's Board 054931
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1944

Signed Thomas M. Beall
By driller performing actual drilling on-site or contractor
Date 3/10/15

(Rev. 05-08)

USE ADDITIONAL SHEETS IF NECESSARY

36.0951317
-115.0631759
NAD 27

(NSPO 3-08) (O) 627