STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 123022
Permit No.
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36848

1. OWNER CC Public Right of Way
MAILING ADDRESS 5005 S. Grand Central Pkwy Las Vegas, NV 89155-0000
ADDRESS AT WELL LOCATION No Address Hacienda & Wellis
Subdivision Name:
County: Clark

2. LOCATION SE ¼ NE ¼ Sec 29 T 21 N/S R 62 E
PERMIT/WAIVER No. MO-3023 (Issued by Water Resources) 161-29-699-013 (Parcel No.)
Latitude 36°5'34.49" Longitude -115°3'52.95"
UTM E N
☐ NAD 27 ☒ NAD 83/WGS 84
Client No. PZ-23

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC ☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Fill A/C / Gravel Base		0	1	1
Silty Clay		1	10	9
Silty Sand	wet	10	12	2
Silty Clay		12	20	8
Silty Sand	wet	20	22	2
Silty Clay		22	40	18

DCNR/DWR/SNBC RECEIVED MAY 15 2015

Date started: 4/22, 20 15
Date completed: 4/22, 20 15

7. Water Level
Static water level: 30'4" feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality: Note Water level influenced by Nearby wells

8. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NA		

9. WELL CONSTRUCTION
Depth Drilled 40 Feet Depth Cased 40 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
7 Inches		0 Feet	40 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2" sch 40 PVC		F 480	0	40

Perforations:
Type of perforation Factory Slots
Size of perforation .020"
From 10 feet to 40 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☒ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☒ Concrete Grout 0 to 6 ☒ Pumped ☐ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 8 to 40 ☐ Pumped ☒ Poured
Type: #12 Silica Sand
Bentonite Chips: ☒ Yes ☐ No 6 to 8 ☐ Pumped ☒ Poured
Type: 3/8 Bentonite Hole Plug

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name (Contractor) E.L.T. Drilling Inc.
Address (Contractor) 4255 W. Post Rd. Las Vegas, NV 89110
Nevada contractor's license number issued by the State Contractor's Board 054931
Nevada driller's license number issued by the Division of Water Resources the on-site driller 1944M
Signed (By driller performing actual drilling on-site or contractor) Thomas A. Beall
Date 5/15/15

(Rev 06-08) USE ADDITIONAL SHEETS IF NECESSARY

36.0929401
-115.0638786
NAD 27

(NSPO 3-08) (O) 627