STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 123625
Permit No.
Basin

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 36851

1. OWNER C.C. Public Right of Way
MAILING ADDRESS 500 S. Grand Central Pkwy
Las Vegas, NV 89155-0000
ADDRESS AT WELL LOCATION None
Hacienda & Mountain Vista
Subdivision Name: Vista County: Clark

2. LOCATION SW ¼ NE ¼ Sec. 29 T. 21 N/S R. 62 E
PERMIT/WAIVER No. MO-3021 (Issued by Water Resources) 161-29-669-011 Parcel No.
Latitude 36°05'34.50" Longitude 115°04'22.65"
UTM E N
☐ NAD 27 ☒ NAD 83/WGS 84
Client # P218

3. WORKED PERFORMED
☒ New Well ☐ Replace ☐ Recondition ☐ Deepen ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test ☐ Municipal/Industrial ☒ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☐ RVC ☐ Air ☒ Other Auger

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
FILL/Lower Aggabex		0	1	1
SILTY CLAY		1	13	12
SILTY SAND	wet	13	18	5
SILTY CLAY		18	25	7
SILTY SAND	wet	25	27	2
SILTY CLAY		27	45	18

DCNR/DWR/SNBO RECEIVED MAY 15 2015

Date started: 5/4, 20 15
Date completed: 5/4, 20 15

7. Water Level
Static water level: 20.5 feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: °F
Quality: Water level influenced by Nearby Dewatering Wells

8. WELL TEST DATA
TEST METHOD: ☒ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
NA		

9. WELL CONSTRUCTION
Depth Drilled 45 Feet Depth Cased 45 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
7 Inches		0 Feet	45 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2" Sch 40 PVC		ASTM F.480	0	45

Perforations
Type of perforation Factory Slots
Size of perforation .020
From 10 feet to 45 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Annular Seal: ☐ Yes ☐ No
☐ Neat Cement to ☐ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☒ Concrete Grout 0 to 6 ☐ Pumped ☒ Poured
☐ ≥30% Bentonite Grout to ☐ Pumped ☐ Poured

Gravel Pack: ☒ Yes ☐ No 8 to 45 ☐ Pumped ☒ Poured
Type: #12 Silica Sand
Bentonite Chips: ☒ Yes ☐ No 6 to 8 ☐ Pumped ☒ Poured
Type: 3/8 Bentonite Hole Plug

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Elite Drilling, Inc. (Contractor)
Address 4255 W. Post Rd. (Contractor)
Las Vegas, NV. 89118
Nevada contractor's license number issued by the State Contractor's Board 054931
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1944-M
Signed Thomas Ball (By driller performing actual drilling on-site or contractor)
Date 5/15/15

(Rev. 05-08) USE ADDITIONAL SHEETS IF NECESSARY

36.0929429
-115.0721285
NAD 27

(NSPO 3-08) (O) 627