

**STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S REPORT**

**OFFICE USE ONLY**  
Log No. 123069  
Permit No. \_\_\_\_\_  
Basin No. \_\_\_\_\_

**PRINT OR TYPE IN BLACK INK ONLY  
DO NOT WRITE ON BACK**

*Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340*

NOTICE OF INTENT NO. 38020  
WELL NAME (if applicable): well#12

1. OWNER/CLIENT NAME Clark County - Public Right of Way  
MAILING ADDRESS 500 South Grand Central PKWY 2nd  
floor Las Vegas NV 84155

DETAILED ADDRESS AT WELL LOCATION Patrick LN. just East of  
McLeod Dr., Clark County, NV.  
Subdivision Name \_\_\_\_\_ County \_\_\_\_\_

2. PLS LOCATION SW ¼ NE ¼ 36 Sec 21S N/S 61 E  
PERMIT/WAIVER NO. DW -1390 161-36-699-027  
Issued by Water Resources Current Parcel No.

Latitude 36 04' 44.61"N UTM E  NAD 27  
Longitude 115 06 27.26"W UTM N  NAD 83/WGS 84

3. WORKED PERFORMED  
 New Well  Deepen: Orig WL# \_\_\_\_\_  
 Replacement: Original well log # \_\_\_\_\_  
 Recondition: Original well log # \_\_\_\_\_

4. PROPOSED USE  
 Domestic  Irrigation  Monitor  
 Mining / Dewater  Com / Ind  Stock  
 Test / Other  Mun / QM  Rec

5. WELL TYPE  
 Auger  Rotary  RVC  
 Air  Mud  Sonic  
Other \_\_\_\_\_

6. LITHOLOGIC LOG				
Material Encountered	Lost Circ.	Water Strata	From	To
Packed Silt-Silty clay			0	4
Silty clay - calicchi			4	18
calicchi - red silty clay			18	20
red silty clay - calicchi			20	25
calicchi - red silty clay			25	28
red silty clay			28	40
Note - Annular Material				
Gravel pack			0	10
DCNR/DWR/SNBO RECEIVED AUG 03 2015				

9. INSTRUCTION				
Depth Drilled:	40	Feet	Depth Cased:	40
HOLE DIAMETER (BIT SIZE)				
	From		To	
24	Inches	0	Feet	40
	Inches		Feet	
	Inches		Feet	
CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8	6	SCH 40	0	40

ANNULAR MATERIALS  
Sanitary Seal  Yes  No  
 Neat Cement \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Cement Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Concrete Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
Bentonite Chips 10 to 12  Pumped  Poured  
 Gravel Pack [ > 0.2 in. ] 12 to 40  Pumped  Poured  
 Sand Pack [ < 0.2 in. ] \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured  
 Other, explain: \_\_\_\_\_  Pumped  Poured

PERFORATIONS:  
Type of perforation: machine slot  
Size of perforation: 0.032  
From 20 Feet To 40 Feet  
From \_\_\_\_\_ Feet To \_\_\_\_\_ Feet  
From \_\_\_\_\_ Feet To \_\_\_\_\_ Feet  
From \_\_\_\_\_ Feet To \_\_\_\_\_ Feet

Date started: 2-Jul , 20 15  
Date completed: 2-Jul , 20 15

7. WATER QUALITIES  
Static water level: 18 Feet below land surface  
Artesian Flow: \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature: \_\_\_\_\_ ° Fahrenheit  
Water Quality: \_\_\_\_\_

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision. This report is true to the best of my knowledge.  
Name Viking Drillers, Inc Contractor  
Address 5950 Granite Lake Drive, Granite Bay, CA 95746 Contractor  
Nevada contractor's license number as issued by the State Contractor's Board. 0034680  
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller) 2351  
Signed: Matthew J. Pappas  
By driller performing actual drilling on site as contractor  
Date: 7/29/15

8. WELL TEST DATA			
Test Method:	G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
<input type="checkbox"/> Bailer			
<input type="checkbox"/> Pump			
<input type="checkbox"/> Air Lift			

36,079,0849  
-115,106,7421  
NAD  
27