STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 123140
Permit No.
Basin 13713

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 73257
WELL NAME (*If applicable*): DW-31

1 OWNER Round Mountain Gold Corp.
MAILING ADDRESS PO Box 480, Round Mountain, NV. 89045

ADDRESS AT WELL LOCATION Round Mountain Mine, Round Mountain, NV
Subdivision Name: *County:* Nye

2 LOCATION SE ¼ SW ¼ Sec 24 T 10N N/S R 43 E
PERMIT/WAIVER No. 68462T *Issued by Water Resources* *Parcel No.*

Latitude
Longitude
UTM E 491282 X NAD 27
N 4283739 ☐ NAD 83/WGS 8

3 TYPE OF WELL
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

Is this well being plugged because a replacement well was drilled? No
If yes, what is replacement well NOI?

Is there an existing well log? Yes
If yes, what is NDWR well log #? 89296

4 *EXISTING WELL CONSTRUCTION*
Depth Drilled 930 Feet Depth Cased 920 Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
22	57.405	.250	0	20
12.75	49.56	.375	20	920

Existing Perforations:
Type of perforation Wire Wrap
Size of perforation 0.08

From	460	feet to	920	feet
From		feet to		feet
From		feet to		feet
From		feet to		feet
From		feet to		feet

5 *WATER LEVEL*
Static water level N/A feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I
Water temperature N/A °F Quality

6 Additional Notes or Comments

Materials Used:
162 bags abandonite
353 bags casing seal
51 bags cement

NAD27
38.704104°N
117.100261°W

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? ☒ yes ☐ no
If well was not cleaned out to total depth, please explain why:

Was the well contaminated? ☐ yes ☒ no
Was the casing pulled? ☐ yes ☒ no If pulled from: feet to feet
Was the casing over drilled? ☐ yes ☒ no
If casing was left in place, please show where additional perforations were made:
Additional Perforations.
Type of perforater used: Holte

From	390	feet to	450	feet	Number of perfs per linear foot	24
From		feet to		feet	Number of perfs per linear foot	
From		feet to		feet	Number of perfs per linear foot	
From		feet to		feet	Number of perfs per linear foot	
From		feet to		feet	Number of perfs per linear foot	
From		feet to		feet	Number of perfs per linear foot	
From		feet to		feet	Number of perfs per linear foot	
From		feet to		feet	Number of perfs per linear foot	
From		feet to		feet	Number of perfs per linear foot	
From		feet to		feet	Number of perfs per linear foot	
From		feet to		feet	Number of perfs per linear foot	
From		feet to		feet	Number of perfs per linear foot	

8 WELL PLUGGING MATERIALS

					Material Used		
From	0	feet to	50	feet	Cement	☐ Pumped	☒ Poured
From	50	feet to	248	feet	Casing seal	☒ Pumped	☐ Poured
From	248	feet to	920	feet	Abandonite	☒ Pumped	☐ Poured
From		feet to		feet		☐ Pumped	☐ Poured
From		feet to		feet		☐ Pumped	☐ Poured
From		feet to		feet		☐ Pumped	☐ Poured

Neat Cement Fluid Weight 16.5 lbs/gal
Bentonite Grout 20 % bentonite

Date Started 18-Aug-15
Date Completed 20-Aug-15

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.
Name Boart Longyear
Contractor
Address 2745 California Ave., SLC., UT 84104
Contractor

Nevada contractor's license number issued by the *State Contractor's Board* 0021976
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 2486
Signed
By driller performing actual drilling on site or contractor
Date 24-Aug-15

RECEIVED 2015 AUG 27 AM 10:58 STATE ENGINEER OFFICE

(Rev. 12-13) **USE ADDITIONAL SHEETS IF NECESSARY** pg. 1 of pg. 1

Plugs well log 89296