STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 123209
Permit No.
Basin No.

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37856
WELL NAME (If applicable): PC155A

1. OWNER/CLIENT NAME Nevada Environmental Responsetas
MAILING ADDRESS 35 East Walker Drive #1550 Chicago IL 60601-2314
DETAILED ADDRESS AT WELL LOCATION 8200 E. Russell Rd.
Henderson, NV, 89122
Subdivision Name: County: Clark

2. PLS LOCATION SW ¼ SW ¼ 30 Sec 21 N/S 63 E
PERMIT/WAIVER NO. MO-3051 (Issued by Water Resources) 160-30-000-003 (Current Parcel No.)
Latitude 36° 05' 16.13" N UTM E
Longitude -114° 59' 33.63" W UTM N
☐ NAD 27 ☑ NAD 83/WGS 84

3. WORKED PERFORMED
☑ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☑ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☑ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Sand w/Gravel and Silt			0'	28'
Silt with Clay and Sand			28'	30'

DCNR/DWR/SNBO
RECEIVED
MAY 21 2015

Date started: 4/20/15, 20 15
Date completed: 4/20/15, 20 15

7. WATER QUALITIES
Static water level: 22 Feet below land surface
Artesian Flow: NA G.P.M. P.S.I.
Water Temperature: NA ° Fahrenheit
Water Quality: Clear

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)

9. INSTRUCTION
Depth Drilled: 30 Feet Depth Cased: 30 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
6.78 ~~8.25~~ Inches		0 Feet	30 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.68	0.154	0	30

ANNULAR MATERIALS
Sanitary Seal ☑ Yes ☐ No

☑ Neat Cement	0 to 11	☑ Pumped	☐ Poured
☐ Cement Grout	to	☐ Pumped	☐ Poured
☐ Concrete Grout	to	☐ Pumped	☐ Poured
☑ Bentonite Chips	11 to 13	☐ Pumped	☐ Poured
☐ Gravel Pack [> 0.2 in.]	to	☐ Pumped	☐ Poured
☑ Sand Pack [< 0.2 in.]	13 to 30	☐ Pumped	☐ Poured
☐ Other, explain:	to	☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: Factory
Size of perforation: 0.02
From 15 Feet To 30 Feet
From Feet To Feet
From Feet To Feet
From Feet To Feet
From Feet To Feet

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name National EWP (Contractor)
Address 5241 Schirlls St. Las Vegas, NV 89118 (Contractor)
Nevada contractor's license number as issued by the State Contractor's Board: 0075355
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller) 2512-LTD
Signed: Bob W (By driller performing actual drilling on site or contractor)
Date: 5/20/15

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.

36.08783387
-114.9918472

NAD 2