

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY  
Log No. 123475  
Permit No. 11368  
Basin

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 39471

1 OWNER Owens Associates LLC  
MAILING ADDRESS P.O. Box 49272, Los Angeles, CA 90049

ADDRESS AT WELL LOCATION 1618 N. Las Vegas Blvd.  
North Las Vegas

2 LOCATION SW 1/4 SW 1/4 Sec 23 T 20S N34R 61 E  
PERMIT/WAIVER No. 11368(FWR) 139-23-402-007  
Issued by Water Resources Parcel No

Subdivision Name County  
Latitude 36.188737 UTM E  NAD 27  
Longitude -115.132328 N  NAD 83/WGS 84

3 TYPE OF WELL  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

Is this well being plugged because a replacement well was drilled? no  
If yes, what is replacement well NOI?  
Is there an existing well log? YES  
If yes, what is NDWR well log #? 6996 / 2867

4 EXISTING WELL CONSTRUCTION  
Depth Drilled 635 Feet Depth Cased 635 Feet

7 WELL PLUGGING PROCEDURE  
Was well cleaned out to total depth?  yes  no  
If well was not cleaned out to total depth, please explain why:

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
12"	28lbs		15"	150'
10"		1/4"	10"	523'
8 5/8"	13lbs		225'	635'

Was the well contaminated?  yes  no  
Was the casing pulled?  yes  no  
Was the casing over drilled?  yes  no  
If casing was left in place, please show where additional perforations were made:  
Additional Perforations

Existing Perforations:

Type of perforation	Size of perforation	feet to	feet
			NA
			NA
From			feet

Perforator Mill Knife

Type of perforator used:	feet to	feet	Number of perfs per linear foot
From 10"		350	2
From		feet	

5 WATER LEVEL  
Static water level Surface feet below land surface  
Artesian flow G.P.M. P.S.I.  
Water temperature 75 °F Quality Clear

8 WELL PLUGGING MATERIALS  
Material Used  
From 635 feet to 0 feet 23 Sack Slurry  Pumped  Poured  
From feet to feet  Pumped  Poured

6 Additional Notes or Comments  
Unable to obtain a G.P.M. or P.S.I.  
The casing was compromised under surface and water was flowing to the surface on outside of casing  
We also Blew out about 30 yards of Sand from about 350 to 635. Casing in that area was non existing  
I would guess it was flowing about 120 gallons an hour.  
Has been successfully plugged  
It took 34 yards of 23sack slurry to plug it to the surface  
DCNR/DWR/SNB0 RECEIVED  
SEP 24 2015

Neat Cement Fluid Weight 23 Sack lbs/gal  
Bentonite Grout % bentonite  
Date Started 8/11/2015  
Date Completed 9/18/2015

9 DRILLER'S CERTIFICATION  
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.  
Name Eagle Drilling LLC. Contractor  
Address 7150 Placid St. Las Vegas, Nv., 89119 Contractor  
Nevada contractor's license number issued by the State Contractor's Board 51266  
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 2399  
Signed [Signature]  
Date 9/21/2015  
By driller performing actual drilling on site or contractor

36.1887668 NAD  
-115.1314935 27