STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 123516
Permit No.
Basin No. 070

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 74211
WELL NAME (*If applicable*):

1. OWNER/CLIENT NAME Steve Veesart
MAILING ADDRESS 1050 Connolly Dr. Apt 9
Elko Nv 89810

DETAILED ADDRESS AT WELL LOCATION 7695 Bea's View Dr.
Winnemucca NV 89445
Subdivision Name: Canyon Run *County:* Humboldt

2. PLS LOCATION NE ¼ SW ¼ 18 Sec 35 N/S 38 E
PERMIT/WAIVER NO. 3538-18-327-005
Issued by Water Resources *Current Parcel No.*

Latitude N40*54'19.712 UTM E ☐ NAD 27
Longitude W117*44'56.265 UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☒ Rotary ☐ RVC
☐ Air ☒ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Sand		No	0	3
Coarse gravel cobbles boulders		No	3	120
Cemented gravel sand clay		No	120	200
Cemented gravel sand clay		Yes	200	320

NAD 27
40.905572°N
117.748000° W

Date started: 27-Oct , 20 15
Date completed: 11/03/15 , 20 15

7. WATER QUALITIES
Static water level: 240 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: 58 ° Fahrenheit
Water Quality: Clear

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
22	N/A	8

9. CONSTRUCTION
Depth Drilled: 320 Feet Depth Cased: 320 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8"	Inches	0	Feet	320	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8"	Steel	.188	0	20
6 5/8"	PVC	Sched 40	20	320

ANNULAR MATERIALS

Sanitary Seal X ☒ Yes ☐ No

☒ Neat Cement	0	to	20	☒ Pumped	☐ Poured
☐ Cement Grout		to		☐ Pumped	☐ Poured
☐ Concrete Grout		to		☐ Pumped	☐ Poured
☒ Bentonite Chips	20	to	50	☐ Pumped	☒ Poured
☒ Gravel Pack [> 0.2 in.]	50	to	320	☐ Pumped	☒ Poured
☐ Sand Pack [< 0.2 in.]		to		☐ Pumped	☐ Poured
☐ Other, explain:		to		☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: slot
Size of perforation: 0.2

From ~~280~~ 260	Feet	To 320	Feet
From	Feet	To	Feet
From	Feet	To	Feet
From	Feet	To	Feet
From	Feet	To	Feet

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.

Name Allied Drilling Inc.
Contractor
Address 5140 Jungo Rd Winnemucca NV
Contractor

Nevada contractor's license number as issued by the *State Contractor's Board:* 76778
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller):* 1563

Signed:
By driller performing actual drilling on site or contractor
Date: 11-4-15

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.