

STATE OF NEVADA  
DIVISION OF WATER RESOURCES  
**WELL DRILLER'S REPORT**

OFFICE USE ONLY  
Log No. 123676  
Permit No. \_\_\_\_\_  
Basin No. \_\_\_\_\_

PRINT OR TYPE IN BLACK INK ONLY  
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 38051  
WELL NAME (if applicable): well#57

1. OWNER/CLIENT NAME Clark County - Public Right of Way  
MAILING ADDRESS 500 South Grand Central PKWY 2nd floor Las Vegas NV 84155

DETAILED ADDRESS AT WELL LOCATION McLeod Dr. just south of East Patrick Lane, Clark County NV  
Subdivision Name: \_\_\_\_\_ County: \_\_\_\_\_

2. PLS LOCATION NW ¼ SE ¼ 36 Sec 21S N/S 61 E  
PERMIT/WAIVER NO. DW-1379 | 162-36-799-009  
Issued by Water Resources Current Parcel No.

Latitude 36 04' 35.00" N UTM E  NAD 27  
Longitude 115. 06' 35.03" W UTM N  NAD 83/WGS 84

3. WORKED PERFORMED  
 New Well  Deepen: Orig WL# \_\_\_\_\_  
 Replacement: Original well log # \_\_\_\_\_  
 Recondition: Original well log # \_\_\_\_\_

4. PROPOSED USE  
 Domestic  Irrigation  Monitor  
 Mining / Geothermal  Com / Ind  Stock  
 Test / Other  Mun / QM  Rec

5. WELL TYPE  
 Auger  Rotary  RVC  
 Air  Mud  Sonic  
Other \_\_\_\_\_

6. LITHOLOGIC LOG				
Material Encountered	Lost Circ	Water Strata	From	To
packed silt-silty clay			0	7
silty clay-silty clay & rock			7	9
silty clay & rock -soft silty clay			9	11
soft silty clay-silty clay			11	15
silty clay- calicchi			15	18
calicchi-silty clay			18	28
silty clay-white clay			28	37
white clay			37	40
Note - Annular Material				
Gravel pack			0	10

9. INSTRUCTION  
Depth Drilled: 40 Feet Depth Cased: 40 Feet

HOLE DIAMETER (BIT SIZE)				
From	To	From	To	To
24	Inches	0	Feet	40
	Inches		Feet	
	Inches		Feet	

CASING SCHEDULE				
Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
8	6	3/8	0	40

ANNULAR MATERIALS

Sanitary Seal  Yes  No

Neat Cement \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured

Cement Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured

Concrete Grout \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured

Bentonite Chips 10 to 12  Pumped  Poured

Gravel Pack [ > 0.2 in. ] 12 to 40  Pumped  Poured

Sand Pack [ < 0.2 in. ] \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured

Other, explain: \_\_\_\_\_ to \_\_\_\_\_  Pumped  Poured

Date started: 21-Aug, 20 15  
Date completed: 21-Aug, 20 15

PERFORATIONS:

Type of perforation: machine slot  
Size of perforation: 0.032

From 20 Feet To 40 Feet  
From \_\_\_\_\_ Feet To \_\_\_\_\_ Feet  
From \_\_\_\_\_ Feet To \_\_\_\_\_ Feet  
From \_\_\_\_\_ Feet To \_\_\_\_\_ Feet

7. WATER QUALITIES  
Static water level: 15 Feet below land surface  
Artesian Flow: \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water Temperature: \_\_\_\_\_ ° Fahrenheit  
Water Quality: \_\_\_\_\_

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision. This report is true to the best of my knowledge.  
Name Viking Drillers, Inc Contractor  
Address 5950 Granite Lake Drive, Granite Bay, CA 95746 Contractor

8. WELL TEST DATA

Test Method:	G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
<input type="checkbox"/> Bailer <input type="checkbox"/> Pump <input type="checkbox"/> Air Lift			

Nevada contractor's license number as issued by the State Contractor's Board: 0034680  
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 2361  
Signed: Matthew J. [Signature]  
Date: 9/29/15  
By driller performing actual logging on site or contractor

36.0764154 NAD  
-115.1089006 27