STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S PLUGGING REPORT

OFFICE USE ONLY
Log No. 123912
Permit No. 57800
Basin 054

Well ID: DW-99-1

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 74481

1 OWNER Cortez Gold Mine
MAILING ADDRESS HC-66-50
Beowawe, NV 89821

ADDRESS AT WELL LOCATION Cortez Gold Mine
Pipeline Pit Area
Subdivision Name: N/A County: Lander

2 LOCATION SW¼ ~~SE NE~~ ¼ Sec 30 T 28N N/S R 47 E
PERMIT/WAIVER No. 57800 (Issued by Water Resources) Parcel No.

Latitude
Longitude
UTM E 116.722923
N 40.265237
☐ NAD 27 ☑ NAD 83/WGS 84

3 TYPE OF WELL
☐ Domestic ☑ Municipal/Industrial ☐ Irrigation ☐ Monitor ☐ Test ☐ Stock

Is this well being plugged because a replacement well was drilled? No
If yes, what is replacement well NOI?

Is there an existing well log? Yes
If yes, what is NDWR well log #? 78299

4 EXISTING WELL CONSTRUCTION
Depth Drilled 1500 Feet Depth Cased 1500 Feet

EXISTING CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
16	42.05	0.250	0	60
8.625	22.36	0.250	+2	1500

Existing Perforations:
Type of perforation Mill Slot
Size of perforation 0.125 X3"

From	feet to	feet
985	1500	

5 WATER LEVEL
Static water level None feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I
Water temperature N/A °F Quality N/A

6 Additional Notes or Comments
Pump was pulled out, Well was dry.

NAD 27
40.2603318
116.722001

7 WELL PLUGGING PROCEDURE
Was well cleaned out to total depth? ☑ yes ☐ no
If well was not cleaned out to total depth, please explain why:

Was the well contaminated? ☐ yes ☑ no
Was the casing pulled? ☐ yes ☑ no
Was the casing over drilled? ☐ yes ☑ no
If casing was left in place, please show where additional perforations were made:

Additional Perforations:
Type of perforater used: Vertical Slot

From	feet to	feet	Number of perfs per linear foot
900	985		2

8 WELL PLUGGING MATERIALS

From	feet to	feet	Material Used	Pumped	Poured
0	50		Neat Cement	☑	☐
50	900		Abandonite	☑	☐
900	1500		Bore Grout	☑	☐
				☐	☐
				☐	☐
				☐	☐

Neat Cement Fluid Weight 15 lbs/gal
Bentonite Grout 20 % bentonite

Date Started November 17,2015
Date Completed November 19, 2015

9 DRILLER'S CERTIFICATION
This well was plugged and abandoned under my supervision and the report is true to the best of my knowledge.

Name Boart Longyear Company (Contractor)
Address P.O. Box 2748 (Contractor)
Elko, NV 89803
Nevada contractor's license number issued by the *State Contractor's Board* 0021976
Nevada driller's license number issued by the Division of Water Resources, the *on-site driller* 1942
Signed William Riley (By driller performing actual drilling on site of contractor)
Date November 24, 2015

RECEIVED 2015 NOV 30 PM 2:06 STATE ENGINEER'S OFFICE

(Rev. 05-06)

USE ADDITIONAL SHEETS IF NECESSARY

Plugging well log 78299