STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 123953
Permit No.
Basin No. 137B

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 73262
WELL NAME (If applicable): AD-15-6

1. OWNER/CLIENT NAME Round Mountain Gold Corp.
MAILING ADDRESS PO Box 480, Round Mountain, NV. 89045

DETAILED ADDRESS AT WELL LOCATION Round Mountain Mine, Round Mountain, NV
Subdivision Name: County: Nye

2. PLS LOCATION NE ¼ SE ¼ 24 Sec 10 N/S 43 E
PERMIT/WAIVER NO. M/O-2007 (Issued by Water Resources) (Current Parcel No.)

Latitude UTM E 492069 ☒ NAD 27
Longitude UTM N 4284292 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Monitor
☒ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☐ Rotary ☒ RVC
☐ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Alluvium			0	230
Clay			230	250
Red-white rock			250	360
White-gray rock			360	540
Gray rock			540	600

RECEIVED 2015 OCT -2 AM 11:58 STATE ENGINEERS OFFICE

NAD27
38.709100°N
117.091214°W

Date started: 21-Sep, 20 15
Date completed: 23-Sep, 20 15

7. WATER QUALITIES
Static water level: N/A Feet below land surface
Artesian Flow: N/A G.P.M. P.S.I.
Water Temperature: N/A ° Fahrenheit
Water Quality: N/A

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☐ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
N/A		N/A	N/A

9. CONSTRUCTION
Depth Drilled: 600 Feet Depth Cased: 600 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
9.875	Inches	0	Feet	20	Feet
6.5	Inches	20	Feet	600	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.95	.218	+1	600

ANNULAR MATERIALS
Sanitary Seal X Yes ☐ No

☒ Neat Cement	0	to	20	☐ Pumped	☐ X Poured
☐ Cement Grout		to		☐ Pumped	☐ Poured
☐ Concrete Grout		to		☐ Pumped	☐ Poured
☒ Bentonite Chips	20	to	40	☒ Pumped	☐ Poured
☐ Gravel Pack [> 0.2 in.]		to		Pumped	☐ Poured
☒ Sand Pack [< 0.2 in.]	40	to	600	☒ Pumped	☐ Poured
☐ Other, explain:		to		☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: Slotted
Size of perforation: 0.020

From	40 Feet	To	600	Feet
From	Feet	To		Feet
From	Feet	To		Feet
From	Feet	To		Feet
From	Feet	To		Feet

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Boart Longyear (Contractor)
Address 2745 California Ave., SLC., UT. 84104 (Contractor)
Nevada contractor's license number as issued by the State Contractor's Board: 0021976
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 2258
Signed: [signature] (By driller performing actual drilling on site or contractor)
Date: 28-Sep-15

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. 1 of pg. 1