STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 123973
Permit No.
Basin No.

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37832
WELL NAME *(If applicable)*: MW-10

1. OWNER/CLIENT NAME: MB REO-NV-Industrial
MAILING ADDRESS: 515 S. Flower St. 44th fl.
Los Angeles, CA 90071

DETAILED ADDRESS AT WELL LOCATION: 3463 Procyon St.
Las Vegas, NV
Subdivision Name: County: Clark

2. PLS LOCATION: NW ¼ NW ¼ 17 Sec 21 N/S 61 E
PERMIT/WAIVER NO. MO-3106 (Issued by Water Resources) 162-17-101-018 (Current Parcel No.)

Latitude 36°07'37.30"N UTM E ☐ NAD 27
Longitude -115°11'17.47"W UTM N ☑ NAD 83/WGS 84

3. WORKED PERFORMED
☑ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☑ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☑ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Silty Sand, Very fine				
Some gravel			1	6
Silty Clay, moist, stiff			6	10
Cemented Sand				
and gravel			10	12
Sandy Clay, partly				
Cemented, damp			12	15
Sandy gravel, very dense				
moist-wet			15	23
Caliche, very hard			23	26

DCNR/DWR/SNRD
RECEIVED
OCT 28 2015

Date started: 10-16, 20 15
Date completed: 10-16, 20 15

7. WATER QUALITIES
Static water level: 18.9 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☑ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
	0	

9. CONSTRUCTION
Depth Drilled: 25 Feet Depth Cased: 25 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8.25 Inches		0 Feet	25 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.375	0.68	0.154	0	25

ANNULAR MATERIALS
Sanitary Seal ☑ Yes ☐ No

☐ Neat Cement		to	☐ Pumped	☐ Poured
☑ Cement Grout	0	to 11	☑ Pumped	☐ Poured
☐ Concrete Grout		to	☐ Pumped	☐ Poured
☑ Bentonite Chips	11	to 13	☐ Pumped	☑ Poured
☐ Gravel Pack [> 0.2 in.]		to	☐ Pumped	☐ Poured
☑ Sand Pack [< 0.2 in.]	13	to 25	☐ Pumped	☑ Poured
☐ Other, explain:		to	☐ Pumped	☐ Poured

25-26 Sand

PERFORATIONS:
Type of perforation: Factory
Size of perforation: .020

From 15 Feet	To 25 Feet		
From Feet	To Feet		
From Feet	To Feet		
From Feet	To Feet		
From Feet	To Feet		

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name: National EWP (Contractor)
Address: 4221 W. Oquendo Rd. Las Vegas, NV 89118 (Contractor)
Nevada contractor's license number as issued by the *State Contractor's Board*: 0075355
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller)*: 2526
Signed: (By driller performing actual drilling on site or contractor)
Date: 10/28/2015

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.

36.127057
-115.1873527
NAD 27