STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 124389
Permit No.
Basin No. 101

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 37917 5
AEI-MW01
WELL NAME (If applicable): MW-A

1. OWNER/CLIENT NAME Department of the Navy
MAILING ADDRESS 4755 Pasture Road, Fallon NV 89496
DETAILED ADDRESS AT WELL LOCATION Same As Owner
Subdivision Name: County: Churchill

2. PLS LOCATION ~~NW~~ ¼ NE ~~SW~~ ¼ SE ~~28~~ 22 Sec 18 N/S 29 E
PERMIT/WAIVER NO. M/O-2039 (Issued by Water Resources) 006-611-01 (Current Parcel No)
Latitude UTM E 2589410.144 ☐ NAD 27
Longitude UTM N 14819455.55 ☑ NAD 83/WGS 84

3. WORKED PERFORMED
☑ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☑ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☑ Auger ☐ Rotary ☐ RVC
☐ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Artificial fill - Class II Base			0	8
Overburden Fill			8	14
Silty sand to clayey sand			14	
verk dark grey				
organic smell				
fine grained, low plasticity				20
NAD 27				
39.408737				
118.707156				

DCNR/DWR/SNBO
RECEIVED
FEB 04 2016

Date started: 9-Jan, 20 16
Date completed: 9-Jan, 20 16

7. WATER QUALITIES
Static water level: 12' Feet below land surface
Artesian Flow: NA G.P.M. NA P.S.I.
Water Temperature: NA ° Fahrenheit
Water Quality: Clear

8. WELL TEST DATA
Test Method: ☐ Bailer ☑ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)

9. CONSTRUCTION
Depth Drilled: 20 Feet Depth Cased: 20 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10.25	Inches	0	Feet	20	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4.500	2.938	0.337	0	20

ANNULAR MATERIALS
Sanitary Seal ☑ Yes ☐ No

☑ Neat Cement	0	to	1.5	☑ Pumped	☐ Poured
☐ Cement Grout		to		☐ Pumped	☐ Poured
☐ Concrete Grout		to		☐ Pumped	☐ Poured
☑ Bentonite Chips	1.5	to	3	☐ Pumped	☑ Poured
☐ Gravel Pack [> 0.2 in.]		to		☐ Pumped	☐ Poured
☑ Sand Pack [< 0.2 in.]	3	to	20	☐ Pumped	☑ Poured
☐ Other, explain:		to		☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: Factory
Size of perforation: 0.02

From		To	
5	Feet	20	Feet
	Feet		Feet
	Feet		Feet
	Feet		Feet
	Feet		Feet

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name National EWP (Contractor)
Address 4221 West Oquendo Road, Las Vegas, NV 89118 (Contractor)
Nevada contractor's license number as issued by the State Contractor's Board: 0075355
Nevada well driller's license number as issued by the Nevada Division of Water Resources (on-site driller): 2512
Signed: Bob H (By driller performing actual drilling on site or contractor)
Date: 2/1/2016

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.