STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 124474
Permit No.
Basin No. 101

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 74451
WELL NAME *(if applicable)*:

1. OWNER/CLIENT NAME Fred Chicadona
MAILING ADDRESS 1250 Roberson In Fallon NV 89406
DETAILED ADDRESS AT WELL LOCATION 1250 Roberson In Fallon NV 89406
Subdivision Name: County Churchill

2. PLS LOCATION ~~SE~~ ¼ ~~SE~~ ¼ ~~20~~ Sec 19 N/S 28 E
PERMIT/WAIVER NO. SE SE 19 008-53-21
Issued by Water Resources *Current Parcel No.*
Latitude UTM E 0338780 ☒ NAD 27
Longitude UTM N 4372927 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☐ New Well ☐ Deepen: Orig WL#
☒ Replacement: Original well log # Non found
☐ Recondition: Original well log #

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☒ Rotary ☐ RVC
☒ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To	Thickness
Brown Sands		X	0	50	50
Black sand & Clay		X	50	70	20
Grey Sands & Clays		X	70	90	20
Brown Sands & Clay		X	90	117	27
NAD 27					
39.492734					
118.874800					

RECEIVED 2016 FEB 29 PM 12:48 STATE ENGINEERS OFFICE

Date started: 2-22-16, 20
Date completed: 2-23-16, 20

9. WELL CONSTRUCTION
Depth Drilled: 117 Feet Depth Cased: 117 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 3/4	Inches	0	Feet	103	Feet
6 5/8	Inches	103	Feet	117	Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.9	.188	+2	117

PERFORATIONS:
Type of perforation: Factory Cut
Size of perforation: 60 thousands 2" Cut
From 110 Feet To 115 Feet
From Feet To Feet
From Feet To Feet

ANNULAR MATERIALS
☐ Sanitary Seal to
☒ Neat Cement 0 to 103 ☒ Pumped ☐ Poured
☐ Cement Grout to ☐ Pumped ☐ Poured
☐ Concrete Grout to ☐ Pumped ☐ Poured
☐ Bentonite Chips to ☐ Pumped ☐ Poured
☐ Bentonite Grout to ☐ Pumped ☐ Poured
☐ 15 % ☐ 20 % ☐ Other, explain:
☐ Gravel Pack [> 0.2 in.] to ☐ Pumped ☐ Poured
☐ Sand Pack [< 0.2 in.] to ☐ Pumped ☐ Poured
☐ Other, explain: to ☐ Pumped ☐ Poured

7. WATER QUALITIES
Static water level: 28 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: Cool ° Fahrenheit
Water Quality: Not tested

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
60		2 Hours

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Webco Corp
Contractor
Address PO Box 888
Contractor

Nevada contractor's license number as issued by the *State Contractor's Board:* 11752
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller):* 2539

Signed: [signature]
By driller performing actual drilling on site or contractor
Date: 2-23-16

(Rev. 08-12)
USE ADDITIONAL SHEETS IF NECESSARY
(NSPO Rev 11-12) Replacing unknown well log
(O) 627