STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 124478
Permit No.
Basin No. 049

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 74044
WELL NAME *(If applicable)*:

1. OWNER/CLIENT NAME KRISTY ANDREWS
MAILING ADDRESS 474 GYPSUM DR
SPRING CREEK, NV 89815

DETAILED ADDRESS AT WELL LOCATION 3663 STATICE ST
BLK 61 LOT 7
Subdivision Name: MVR 5 *County:* ELKO

2. PLS LOCATION SW ¼ SW ¼ 35 Sec 35N N/S 55 E
PERMIT/WAIVER NO. 037-061-007
Issued by Water Resources *Current Parcel No.*

Latitude UTM E 605086 ☒ NAD 27
Longitude UTM N 4524834 ☐ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☒ Rotary ☐ RVC
☒ Air ☐ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
ALLUVIUM			0	20'
SANDES & GRAVELS			20'	260'
BIGGER GRAVLES			260'	360'

RECEIVED 2016 FEB 29 PM 2:55 STATE OF NEVADA ENGINEERS OFFICE

NAD 27
40.869742
115.752986

Date started: 17-Feb , 20 16
Date completed: 19-Feb , 20 16

7. WATER QUALITIES
Static water level: 247' Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: 56 ° Fahrenheit
Water Quality: GOOD

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☒ Air Lift

	G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
360'	30		2HR
320'	22		1HR
300	16		1HR
280'	10		.5HR
270'	5		.5HR

9. CONSTRUCTION
Depth Drilled: 360' Feet Depth Cased: 360' Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
10 5/8	Inches	0	Feet	360'	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6.625	13	.188	+1.5	360'

ANNULAR MATERIALS
Sanitary Seal ☒ Yes ☐ No

☐ Neat Cement		to		☐ Pumped	☐ Poured
☒ Cement Grout	5'	to	25'	☐ Pumped	☒ Poured
☐ Concrete Grout		to		☐ Pumped	☐ Poured
☒ Bentonite Chips	25'	to	55'	☐ Pumped	☒ Poured
☒ Gravel Pack [> 0.2 in.]	55'	to	360'	☐ Pumped	☒ Poured
☐ Sand Pack [< 0.2 in.]		to		☐ Pumped	☐ Poured
☐ Other, explain:		to		☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: PLASMA CUT
Size of perforation: 3/16" X 4" 6 ROWS

From 320'	Feet	To 360'	Feet
From	Feet	To	Feet
From	Feet	To	Feet
From	Feet	To	Feet
From	Feet	To	Feet

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name HACKWORTH DRILLING INC. *Contractor*
Address P.O. BOX 850, ELKO, NV 89803 *Contractor*
Nevada contractor's license number as issued by the *State Contractor's Board:* 020582
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller):* 2329
Signed: *By driller performing actual drilling on-site or contractor*
Date: 2/22/2016

(Rev. 12-13) **USE ADDITIONAL SHEETS IF NECESSARY** pg. of pg.