STATE OF NEVADA
DIVISION OF WATER RESOURCES
WELL DRILLER'S REPORT

OFFICE USE ONLY
Log No. 124490
Permit No.
Basin No. 101

PRINT OR TYPE IN BLACK INK ONLY
DO NOT WRITE ON BACK

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 634.340

NOTICE OF INTENT NO. 74613
WELL NAME *(If applicable)*:

1. OWNER/CLIENT NAME Kasm Construction, LLC.
MAILING ADDRESS 782 Divot Dr.
Fernley, NV 89408

DETAILED ADDRESS AT WELL LOCATION 1197 Skyridge Dr.
Fallon, NV 89406
Subdivision Name: *County:* Churchill

2. PLS LOCATION NE ¼ SW ¼ 20 Sec 19 N/S 28 E
PERMIT/WAIVER NO. 008-176-67
Issued by Water Resources *Current Parcel No.*

Latitude 39.49509 UTM E ☐ NAD 27
Longitude 118.87023 UTM N ☒ NAD 83/WGS 84

3. WORKED PERFORMED
☒ New Well ☐ Deepen: Orig WL#
☐ Replacement: Original well log #
☐ Recondition: Original well log #

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Monitor
☐ Mining / Dewater ☐ Com / Ind ☐ Stock
☐ Test / Other ☐ Mun / QM ☐ Rec

5. WELL TYPE
☐ Auger ☒ Rotary ☐ RVC
☐ Air ☒ Mud ☐ Sonic
☐ Other

6. LITHOLOGIC LOG

Material Encountered	Lost Circ.	Water Strata	From	To
Brown Sand			0	18
Sand/Clay			18	32
Brown Sand			32	50
Black Sand			50	58
Brown Sand			58	63
Fine Brown Sand/Green Sand			63	75
Gray Sand			75	91
Brown Sand		X	91	105

NAD 27
39.495174
118.869241

Date started: 4-Feb , 20 16
Date completed: 4-Feb , 20 16

7. *WATER QUALITIES*
Static water level: 28 Feet below land surface
Artesian Flow: G.P.M. P.S.I.
Water Temperature: ° Fahrenheit
Water Quality:

8. WELL TEST DATA
Test Method: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Recorded Time (Hours)
15		1

9. *INSTRUCTION*
Depth Drilled: 105 Feet Depth Cased: 105 Feet

HOLE DIAMETER (BIT SIZE)

		From		To	
12	Inches	0	Feet	105	Feet
	Inches		Feet		Feet
	Inches		Feet		Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.92	.188	+2	25
6	4.1	SDR21	25	105

ANNULAR MATERIALS
Sanitary Seal ☒ Yes ☐ No

☒ Neat Cement	0	to	100	☒ Pumped	☐ Poured
☐ Cement Grout		to		☐ Pumped	☐ Poured
☐ Concrete Grout		to		☐ Pumped	☐ Poured
☐ Bentonite Chips		to		☐ Pumped	☐ Poured
☒ Gravel Pack [> 0.2 in.]	100	to	105	☐ Pumped	☒ Poured
☐ Sand Pack [< 0.2 in.]		to		☐ Pumped	☐ Poured
☐ Other, explain:		to		☐ Pumped	☐ Poured

PERFORATIONS:
Type of perforation: Saw Cut
Size of perforation: 1/8.

From	Feet	To	Feet
102	Feet	105	Feet
	Feet		Feet
	Feet		Feet
	Feet		Feet
	Feet		Feet

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision. This report is true to the best of my knowledge.
Name Parsons Drilling, Inc. (Contractor)
Address P.O. Box 1265 Fallon, NV 89407 (Contractor)
Nevada contractor's license number as issued by the *State Contractor's Board:* 29064
Nevada well driller's license number as issued by the *Nevada Division of Water Resources (on-site driller):* 2509
Signed: *(By driller performing actual drilling on site or contractor)*
Date: 2/29/2016

(Rev. 12-13) USE ADDITIONAL SHEETS IF NECESSARY pg. of pg.