WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

CLARENCE PYLES (PYLES + REAMER)

Log No. 13158
Rec. 19
Well No.
Permit No. 27265
Do not fill in

Owner: Max L. Tenesch Driller: Patrick . Thompson

Address: 4721 Baxter Place Address: 217 so. 26th st. L.V.N. Lic. No. 122

Location of well: NE ¼ NW ¼ Sec. 4, T. 21 N/S, R. 60 E, in Clark County

or 27265

Water will be used for: Domestic Total depth of well: 550'

Size of drilled hole: 12" to 65' - 10" from 65 to 550' Weight of casing per linear foot: 12#

Thickness of casing: 10 guage Temp. of water: cool

Diameter and length of casing: 8" dia. - 551' length
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure:

If nonflowing well give depth of standing water from surface: 456'

If flowing well describe control works:
(Type and size of valve, etc.)

Date of commencement of well: Oct. 27, 1959 Date of completion of well: Nov. 30, 1959

Type of well rig: Cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	465	465	cemented gravel
465	470	5	cemented gravel - water
470	475	5	cemented gravel
475	483	8	cemented gravel - water
483	515	32	cemented gravel
515	530	15	cemented gravel - water
530	545	15	cemented gravel
545	550	5	cemented gravel - water

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 515 to 530 ft.

Other aquifers: 465 - 470
475 - 483
545 - 550

First water at 465 feet.

Casing perforated

from 450 to 550 ft.

Size of perforations

3/16 x 12 - 4 rows

919