


WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY



Log No. 14217
 Rec. 19
 Well No. _____
 Permit No. 27486
Do not fill in

Owner Disk Hurlbut Driller Patrick H. Thompson

Address 1202 N.W. 17th Ave. Portland, Ore. Address 217 S. 26th St., LVN. Lic. No. 192

Location of well: SE 1/4, SE 1/4 Sec. 33, T. 20N/S, R. 42E, in Clark County
 or 27486

Water will be used for Domestic Total depth of well 150'

Size of drilled hole 2" to 50' - 10" from 50' to 150' Weight of casing per linear foot 12#

Thickness of casing 10 gauge Temp. of water cool

Diameter and length of casing 8-5/8" dia. - 151' length =
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure. _____

If nonflowing well give depth of standing water from surface 22'

If flowing well describe control works _____
(Type and size of valve, etc.)

Date of commencement of well MARCH 20, 1961 Date of completion of well MARCH 23, 1961

Type of well rig 71 Star -- Cable tools

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	30	30	Sandy Clay
30	50	20	Sand w/ streaks of gravel water
50	110	60	sandy brown clay - water
110	122	12	loose gravel - water
122	143	21	sandy brown clay
143	150	7	brown clay

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 50 to 110 ft.

Other aquifers 30 - 50

110 - 122

First water at 30 feet.

Casing perforated

from 70 to 150 ft.

Size of perforations

3/16 x 12 - 4 rows



