WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 14927
Rec. ..... 19.....
Well No. .....
Permit No. .....
Do not fill in

Owner: Mr Peterson Driller: Mel.Meyer

Address: Glendale rd.Sparks, Address: I20 Moana Lane Reno, Lic. No. 3

Location of well: ....¼....¼ Sec. 7, T. 19 N/S, R 20 E, in Washoe County

or Rear Of new store by P.F.E.ice loading yard Glendale rd.Sparks,

Water will be used for: Store Total depth of well: 33'

Size of drilled hole: 6" Weight of casing per linear foot: 20#

Thickness of casing: 5/I6" Temp. of water: Cold

Diameter and length of casing: 6"id 33¼'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure .....

If nonflowing well give depth of standing water from surface: 6'

If flowing well describe control works .....
(Type and size of valve, etc.)

Date of commencement of well: 4-7-50 Date of completion of well: 4-8-50

Type of well rig: Cable Tool

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	I0	I0	Rock-Sand
I0	I7	7	Sandy Clay
I7	23	5	Rock-Sand
23	26	3	Clay
26	30	4	Rock-Sand
30	33	3	Sand

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)
from 26 to 31 ft.

Other aquifers 8' -I0

First water at 8' feet.

Casing perforated
from 27 to 3I ft.

Size of perforations
4"cutting torch
9 slots

Log 14927

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
6"id	8"	32'7"	33'3"	Std Steel Pipe w/t Case Hard Drive Shoe With Welded Joints

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Air Compressor 2Hrs Jet

50 Gpm

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed.....
Well Driller

By Mel Meyer

License No. 3

Dated 4-23-50, 19.....

(Not to be filled in by Driller)