

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

COPY OF LOG # 3264

Basin 8 3

Log No. 15008  
 Re. \_\_\_\_\_ 19\_\_\_\_\_  
 Well No. \_\_\_\_\_  
 Permit No. \_\_\_\_\_  
*Do not fill in*

Owner Clifford Head Driller MEL MEYER COMPANY

Address 587 Sullivan Lane Sparks, Nev. Address 190 Hoana Lane Reno Lic. No. 3

Location of well: NE 1/4 NE 1/4 Sec. 1, T. 18 N/S, R. 20 E, in Washoe County  
 or Off old Virginia City Road PROBABLY T. 17 N.

Water will be used for Domestic Total depth of well 161'

Size of drilled hole 6 5/8" O. D. Weight of casing per linear foot 12.89

Thickness of casing .188 Temp. of water Cold

Diameter and length of casing 6" x 161'  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure. \_\_\_\_\_

If nonflowing well give depth of standing water from surface. 93'

If flowing well describe control works. \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well 6/17/35 Date of completion of well 6/21/35

Type of well rig Cable Tool

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	85	85	Rock and brown clay.
85	104	19	Rock and brown clay
104	125	21	Pink rock and clay
125	146	21	Pink rock and clay
146	161	15	Brown rock, water

Water-bearing Formation, Casing Perforations, Etc.

---

Chief aquifer (water-bearing formation)  
 from 146 to 166 ft.

Other aquifers \_\_\_\_\_

---

First water at 146 feet.

Casing perforated  
 from 131 to 161 ft.

Size of perforations  
1/16" x 6"



