

Valley Electric Assoc., Inc.  
**WELL LOG AND REPORT TO THE STATE**  
**ENGINEER OF NEVADA**

PLEASE COMPLETE THIS FORM IN ITS ENTIRETY

Log No. 15489  
 Rec. 19  
 Well No. \_\_\_\_\_  
 Permit No. 29537  
*Do not fill in*



Owner ~~Adams Valley Co-Op~~ Driller Patrick H. Thompson

Address Las Vegas, Nevada Address 217 S. 26th St. L.V.N. Lic. No. 192

Location of well: NE 1/4 NW 1/4 Sec. 27, T20N/S, R53E, in Nye County  
NE 30

Water will be used for Domestic 29537 Total depth of well 200'

Size of drilled hole 12" to 50' - 10" from 50' to 200' Weight of casing per linear foot 17#

Thickness of casing 3/16 Temp. of water cold

Diameter and length of casing 8" dia. -- 201' length  
 (Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure. \_\_\_\_\_

If nonflowing well give depth of standing water from surface 86'

If flowing well describe control works. \_\_\_\_\_  
 (Type and size of valve, etc.)

Date of commencement of well Dec. 5, 1962 Date of completion of well Dec. 21, 1962

Type of well rig Cable tools

**LOG OF FORMATIONS**

| From feet | To feet | Thickness feet | Type of material    |
|-----------|---------|----------------|---------------------|
| 0         | 6       | 6              | Gravel & boulders   |
| 6         | 12      | 6              | Brown clay          |
| 12        | 45      | 33             | Brown clay & gravel |
| 45        | 60      | 15             | Brown clay          |
| 60        | 200     | 140            | Cemented gravel     |

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 86 to 200 ft.

Other aquifers \_\_\_\_\_

First water at 86 feet.

Casing perforated

from 90 to 200 ft.

Size of perforations

3/8 x 3 - 4 rows

