

# WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 5713  
 Date MAR 14 1960  
 Well No. \_\_\_\_\_  
 Permit No. 15919  
*Do not fill in*

Owner Lyle L. Frey Driller Allen E. Hosack  
 Address Star Rt. Box 2 Winnemucca, Nevada Address \_\_\_\_\_ Lic. No. 62  
 Location of well: NE 1/4 SE 1/4 Sec 29, T41 N 6 R37 E, in Humboldt County \_\_\_\_\_  
 or \_\_\_\_\_  
 Water will be used for Irrigation & Domestic Total depth of well 138'  
 Size of drilled hole 14" Weight of casing per linear foot 45 lbs. (14" OD)  
 Thickness of casing 14" O.D. was 5/16" Temp. of water \_\_\_\_\_  
 Diameter and length of casing The 98' of 18" O.D. pipe & 138' of 14" O.D. pipe  
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)  
 If flowing well give flow in c.f.s. or g.p.m. and pressure \_\_\_\_\_  
 If nonflowing well give depth of standing water from surface 53'  
 If flowing well describe control works \_\_\_\_\_  
(Type and size of valve, etc.)  
 Date of commencement of well April, 1950 Date of completion of well May, 1950  
 Type of well rig Cable Tools

### LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material	Water-bearing Formation, Casing Perforations, Etc.
0	98	98	Unknown	
	98	101	Clay	
	101	136	Small gravel & some sand	Chief aquifer (water-bearing formation)
	136	138	Clay	from <u>98</u> to <u>136</u> ft.
Replaced by well log 124778 Plugged by well log 124957				Other aquifers _____
				First water at _____ feet.
				Casing perforated
				from <u>53'</u> to <u>136</u> ft.
				Size of perforations
				<u>3/16" x 3"</u>