

**WELL DRILLERS REPORT**

Please complete this form in its entirety

1. OWNER Kenneth H. Earp ADDRESS P.O. Box 431  
Winnemucca, Nevada 89445  
Battle Creek

2. LOCATION SE 1/4 SW 1/4 Sec. 2 T. 40 N S R. 27 E Humboldt County  
 PERMIT NO. \_\_\_\_\_

3. TYPE OF WORK	4. PROPOSED USE	5. TYPE WELL
New Well <input checked="" type="checkbox"/> Recondition <input type="checkbox"/>	Domestic <input checked="" type="checkbox"/> Irrigation <input type="checkbox"/> Test <input type="checkbox"/>	Cable <input type="checkbox"/> Rotary <input checked="" type="checkbox"/>
Deepen <input type="checkbox"/> Other <input type="checkbox"/>	Municipal <input type="checkbox"/> Industrial <input type="checkbox"/> Stock <input type="checkbox"/>	Other <input type="checkbox"/> Reverse <input type="checkbox"/>

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Conductor		0	10	
Sand, gravel, rock		10	20	
Sand, gravel, rock		20	42	
Clean sand&gravel, rock		42	55	
Sand gravel, dark clay		55	57	
Coarse sand, gravel		57	59	
Light clay		59	63	
Coarse sand, gravel		63	68	
Coarse sand, gravel, dk. clay		69	80	
Sand, gravel, some clay		80	84	
Dk. clay, some sand&gravel		84	92	
1/2 sand&gravel, 1/2 clay		92	95	
Dk. clay, some sand		95	98	
Gravel & coarse sand		98	110	
Clay light br., sand&gravel		110	112	
Coarse sand & gravel		112	117	
Sand, gravel, Dk. clay		117	119	
Sand&gravel--Water--		119	122	
Clay-light Brown		122	125	
Sand, gravel, clay		125	126	
Sand, gravel "coarse", some 4"-5" cobbles-water		126	136	
Sand, gravel, lt. br. clay		136	137	
Clay		137	140	
Sand & Clay		140	142	
Sand, gravel, some cobbles, 4"-5" & Water			142	

8. WELL CONSTRUCTION

Diameter hole 20 inches Total depth 142 feet  
 Casing record \_\_\_\_\_  
 Weight per foot \_\_\_\_\_ Thickness \_\_\_\_\_

Diameter	From	To
<u>8</u> inches	<u>0</u> feet	<u>142</u> feet
_____ inches	_____ feet	_____ feet
_____ inches	_____ feet	_____ feet
_____ inches	_____ feet	_____ feet
_____ inches	_____ feet	_____ feet
_____ inches	_____ feet	_____ feet

Surface seal: Yes  No  Type concrete  
 Depth of seal 50 Feet \_\_\_\_\_ feet  
 Gravel packed: Yes  No   
 Gravel packed from 50 feet to 142 feet

Perforations:  
 Type perforation \_\_\_\_\_  
 Size perforation 1/8  
 From 50 feet to 142 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Date started 5/9/78, 19\_\_\_\_\_  
 Date completed 5/12/78, 19\_\_\_\_\_

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump
	<u>20</u>	<u>120</u>	<u>48 hrs</u>

9. WATER LEVEL

Static water level 33 Feet below land surface  
 Flow \_\_\_\_\_ G.P.M.  
 Water temperature \_\_\_\_\_ ° F. Quality \_\_\_\_\_

10. DRILLERS CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Lloyd Gibbons  
 Address Winnemucca, Nevada  
 Nevada contractor's license number 15234  
 Nevada driller's license number 791  
 Signed [Signature]  
 Date 12/1/78

BAILER TEST

G.P.M.	Draw down	feet	hours