WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLERS REPORT

Please complete this form in its entirety

OFFICE USE ONLY
Log No. 20749
Permit No. 48625
Basin

1. OWNER Carson City #16 ADDRESS Well is located on the NE corner of the intersecton of Mills rd + Centennial Park drive.

2. LOCATION ~~SW~~ NE ¼ ~~NE~~ SW ¼ Sec. 2 T. 15 N/S R. 20 E. C.C. County
PERMIT NO. 2-520-15

3. TYPE OF WORK			4. PROPOSED USE			5. TYPE WELL	
New Well ☒	Recondition ☐		Domestic ☐	Irrigation ☐	Test ☒	Cable ☐	Rotary ☒
Deepen ☐	Other ☐		Municipal ☐	Industrial ☐	Stock ☐	Other ☐	

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sandy top soil		0	4'	4'
Yellow Clay (Sticky)		4'	28'	24'
Sand & Gravel		28'	29'	1'
Yellow Clay		29'	60'	31'
Blue Clay		60'	68'	8'
Sandy		68'	70'	2'
Clay (Blue & Brown layers)		70'	78'	8'
Clay (Blue & Brown) Sand Lenses		78'	118'	40'
Sand		118'	121'	3'
Clay with traces of Sand		121'	130'	9'
Bluish Clay / Small Sand Lenses		130'	140'	10'
Clay / Sand Lenses		140'	148'	8'
Sand & Sandy Clay		148'	152'	4'
Sand Streaks (Small) White Clay		152'	160'	8'
Clay / Sand / Chip Gravel		160'	170'	10'
Cemented Sand / Clay Fill		170'	180'	10'
Cemented Sand / Chip Gravel / Clay		180'	190'	10'
Yellow Clay / Sand & Gravel Chips		190'	200'	10'
70% Yellow Clay / Sand & Gravel Chips / Cobbles		200'	210'	10'
Clay / Cobbles / Sand & Gravel		210'	220'	10'
Brown Clay / More Sand		220'	230'	10'
Sand & Clay Lenses		230'	240'	10'
Sand & Clay in Alt. Layers		240'	250'	10'
Sand & Clay in Alt. Layers		250'	260'	10'
Alternating Layers		260'	270'	10'
Clay & Sand Lenses		270'	280'	10'
Clay & Sand Layers		280'	290'	10'

Date started January 1st, 19 80
Date completed January 16, 19 80

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump
Air Lift	75	—	16

BAILER TEST

G.P.M. ..... Draw down ..... feet ..... hours
G.P.M. ..... Draw down ..... feet ..... hours
G.P.M. ..... Draw down ..... feet ..... hours

8. WELL CONSTRUCTION

Diameter hole 9 7/8, 7 7/8 inches Total depth 430 feet
Casing record 339' x 6 5/8
Weight per foot ..... Thickness 10 ga.

Diameter	From	To
6 5/8 inches	+1 feet	338 feet
inches	feet	feet
inches	feet	feet
inches	feet	feet
inches	feet	feet
inches	feet	feet

Surface seal: Yes ☒ No ☐ Type Grout
Depth of seal 55 feet
Gravel packed: Yes ☒ No ☐
Gravel packed from 55 feet to 340 feet

Perforations:
Type perforation Factory Milled
Size perforation 3/32
From 88' to 101' ~~feet to~~ 310 to 320' feet
From 120' to 131' ~~feet to~~ feet
From 148 to 171 ~~feet to~~ feet
From 211' to 223' ~~feet to~~ feet
From 270 to 293' ~~feet to~~ feet

9. WATER LEVEL

Static water level 10 Feet below land surface
Flow ..... G.P.M.
Water temperature Cool ° F. Quality Clear

10. DRILLERS CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.

Name Enloe Drilling Co.
Address Rt. 3, Box 47 A, Susanville
Nevada contractor's license number 4739 A
Nevada driller's license number 794
Signed Jim V. Enloe
Date 1/25/80

USE ADDITIONAL SHEETS IF NECESSARY

5471