WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Now Ron Floyd (1980)

Log No. 21357
Rec. 194
Well No. 35517
Permit No. 13697
Do not fill in

Owner ~~Gerhard Strob~~ Driller Tom Miller

Address Canoga, Calif. Address 275 Basic, Henderson Lic. No. 129

Location of well: S.E¼N.E¼ Sec. 18, T. 21 N/S, R. 54 E, in Nye County

or

Water will be used for Irrigation Total depth of well 400

Size of drilled hole 18" Weight of casing per linear foot 12 gage

Thickness of casing 12 gage Temp. of water

Diameter and length of casing 14" I.D. 354
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface 32 ft

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well March 24-54 Date of completion of well April 7-54

Type of well rig 72 Spud Star Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	8	8	Top Soil
8	37	29	Brown Clay
37	47	10	Water Sand
47	55	8	Brown Clay
55	65	10	Grey Water Sand
65	70	5	Ceolichia
70	295	225	Brown Clay
295	302	7	Black Water Sand
302	400	98	Brown Clay

(OVER)

Water-bearing Formation, Casing Perforations, Etc.
32-356

Chief aquifer (water-bearing formation)
from 37 to 47 ft.

Other aquifers 55-65
295-302

First water at 37 feet.

Casing perforated
from 32 to 356 ft.

Size of perforations
¼ X 3

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
14½ I.D	0	356	356	

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

WELL DRILLERS STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed.....
Well Driller

By.....

License No. 129

Dated April 9, 1954

(Not to be filled in by Driller)