WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

OFFICE USE ONLY
Log No. 22688
Permit No. 42479
Basin

CORRECTED COPY

Well #7

WELL DRILLERS REPORT

Please complete this form in its entirety

1. OWNER Anaconda Copper Co. Nevada Moly Project ADDRESS Post Office Box 1268 Tonopah, Nevada 89049

2. LOCATION SE ¼ SE ¼ Sec. 2 T. 5 N/~~S~~ R. 41 E. Nye County
PERMIT NO. 42479

3. TYPE OF WORK
New Well ☒ Recondition ☐
Deepen ☐ Other ☐

4. PROPOSED USE: Mining
Domestic ☐ Irrigation ☐ Test ☐
Municipal ☐ Industrial ☐ Stock ☐

5. TYPE WELL
Cable ☐ Rotary ☒
Other ☐

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Sand		0	20	20
Sand & gravel		20	75	55
Boulders & lg. gravel		75	85	10
Sand, gravel, boulders		85	124	39
Sand & fine gravel		124	125	1
Large gravel		125	140	15
Sand & gravel		140	180	40
Grav., sand & boulders		180	251	71
Boulders		251	266	15
Sand & gravel		266	327	61
Cem. sand & gravel		327	393	66
Boulders		393	407	14
Sand & gravel		407	427	20
Cem. gravel		427	447	20
" " &sandstone stks		447	467	20
" " stks tan clay		467	487	20
Tan sandy clay & gravel		487	527	40
Sand & gravel		527	567	40
Cem. sand & gravel		567	587	20
Sandy tan clay & grav.		587	624	37
Sand & fine gravel		624	684	60
Tan clay, sand & grav.		684	784	100
Tan sandy clay		784	812	28
Sand & gravel		812	884	72
Tan clay, sand & grav.		884	1164	280
Grey sndy clay & grav.		1164	1264	100
Gravel & sand		1264	1294	30

Date started January 9, 19 81
Date completed March 25, 19 81

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump

BAILER TEST
G.P.M. ..... Draw down ..... feet ..... hours
G.P.M. ..... Draw down ..... feet ..... hours
G.P.M. ..... Draw down ..... feet ..... hours

8. 36"-195' WELL CONSTRUCTION
Diameter hole 28 inches Total depth 1207 feet
Casing record
Weight per foot Thickness .250

Diameter	From	To
28 inches	+1 feet	195 feet
20 inches	+1 feet	1207 feet
inches	feet	feet
inches	feet	feet
inches	feet	feet
inches	feet	feet

Surface seal: Yes ☒ No ☐ Type Cement
Depth of seal 100' & 190-195' feet
Gravel packed: Yes ☒ No ☐
Gravel packed from 100 feet to 1207 feet

Perforations:
Type perforation Mill slots
Size perforation 1/8x3 dbl cut 20 rows
From 684 feet to 1207 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

9. WATER LEVEL
Static water level 490 Feet below land surface
Flow G.P.M.
Water temperature ° F. Quality

10. DRILLERS CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name THOMPSON DRILLING CO., INC.
Address 3215 Cinder Lane Las Vegas, Nevada 89103

Nevada contractor's license number 4286A

Nevada driller's license number 582

Signed Richard K. Thompson

Date March 31, 1981
(CORRECTED COPY)

USE ADDITIONAL SHEETS IF NECESSARY

O-627