

10-87

**WELL DRILLERS REPORT**

Please complete this form in its entirety

1. OWNER Don & Sandy DesJardin ADDRESS 2040 Manzanita Reno, Nev.  
lot 21 Unit 1 Lakeridge  
 2. LOCATION ne 1/4 nw 1/4 Sec. 26 T. 19 N 19 E Washoe County  
 PERMIT NO. ....

3. TYPE OF WORK  
 New Well  Recondition   
 Deepen  Other   
 4. PROPOSED USE  
 Domestic  Irrigation  Test   
 Municipal  Industrial  Stock   
 5. TYPE WELL  
 Cable  Rotary   
 Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
sandy loam		0	1	1
yellow brown clay mixed with rock		1	10	9
yellow brown sandy clay mixed with sm. rock		10	105	95
dk. grey clay		105	125	20
lt. grey sandy clay mixed with ash		125	135	10
blue grey soft sandstone mixed / lt. grey claystone mixture of red claystone		135	150	15
lt. grey claystone & blue grey sandstone		150	180	30
Mix of red & dk. grey claystone		150	180	15
ash & blue grey sandstone		180	195	15
dk. grey claystone hard		195	205	10
" " " / blue grey		110	205	90
granite hard		110	205	90

8. WELL CONSTRUCTION  
 Diameter hole 8 inches Total depth 295 feet  
 Casing record.....  
 Weight per foot..... Thickness 188  

Diameter	From	To
<u>8</u> inches	<u>+1.2</u> feet	<u>295</u> feet
..... inches	..... feet	..... feet
..... inches	..... feet	..... feet
..... inches	..... feet	..... feet
..... inches	..... feet	..... feet
..... inches	..... feet	..... feet

 Surface seal: Yes  No  Type.....  
 Depth of seal 70 feet  
 Gravel packed: Yes  No   
 Gravel packed from..... feet to..... feet  
 Perforations:  
 Type perforation factory sawed  
 Size perforation 1/8 X 4  
 From 273 feet to 295 feet  
 From..... feet to..... feet  
 From..... feet to..... feet  
 From..... feet to..... feet  
 From..... feet to..... feet

Date started Oct. 8, 1982  
 Date completed Oct. 16, 1982

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump
	<u>20</u>	<u>0</u>	<u>4</u>

BAILER TEST  
 G.P.M. .... Draw down.....feet ..... hours  
 G.P.M. .... Draw down.....feet ..... hours  
 G.P.M. .... Draw down.....feet ..... hours

9. WATER LEVEL  
 Static water level 110 Feet below land surface.....  
 Flow 20 G.P.M.  
 Water temperature 203 ° F. Quality good

10. DRILLERS CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name David E. Ballard  
 Address 15000 Perlite Dr. Reno 89511  
 Nevada contractor's license number 14170  
 Nevada driller's license number 1274  
 Signed David E. Ballard  
 Date Oct. 24, 1982