WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLERS REPORT

Please complete this form in its entirety

OFFICE USE ONLY
Log No. 24369
Permit No.
Basin

1. OWNER Patrick & Jane Schormmar ADDRESS P. O. Box 1711 Winnemucca, Nv.
Parcel C

2. LOCATION ¼ SE ¼ Sec. 12 T. 35N N/S R. 37 E. Humboldt County
PERMIT NO.

3. TYPE OF WORK
New Well ☒ Recondition ☐
Deepen ☐ Other ☐

4. PROPOSED USE
Domestic ☒ Irrigation ☐ Test ☐
Municipal ☐ Industrial ☐ Stock ☐

5. TYPE WELL
Cable ☒ Rotary ☐
Other ☐

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Soil brown-sandy		0	2	2
Gravel brown		2	51	49
Gravel-w-strips of gravel		51	74	23
Clay brown sandy		74	86	12
Gravel brown		86	99	13
Clay-w-strips of sand & gravel brown	WB	99	130	31

Date started Jan. 18, 19 83
Date completed Feb. 3, 19 83

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump

BAILER TEST
G.P.M. 40 Draw down 2 feet 1½ hours
G.P.M. Draw down feet hours
G.P.M. Draw down feet hours

8. WELL CONSTRUCTION
Diameter hole 8 inches Total depth 130 feet
Casing record eight inch
Weight per foot 15 Thickness 156

Diameter	From	To
8 inches	0 feet	130 feet
inches	feet	feet
inches	feet	feet
inches	feet	feet
inches	feet	feet
inches	feet	feet

Surface seal: Yes ☒ No ☐ Type cement
Depth of seal Fifty feet
Gravel packed: Yes ☐ No ☒
Gravel packed from feet to feet

Perforations:
Type perforation Punch
Size perforation 4 inch by 1/8 inch
From 98 feet to 130 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

9. WATER LEVEL
Static water level 82 Feet below land surface
Flow 40 G.P.M.
Water temperature 54 ° F. Quality good

10. DRILLERS CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.

Name T & R WELL DRILLING
Address 9015 S. Grassvally Rd. Winnemucca
Nevada contractor's license number 017721
Nevada driller's license number 1190
Signed Tom Stite
Date Febuary 3, 1983

USE ADDITIONAL SHEETS IF NECESSARY

O-627