



**WELL DRILLERS REPORT**

Please complete this form in its entirety

PRINT OR TYPE ONLY

NOTICE OF INTENT NO. 13346

1. OWNER LARRY FISHER ADDRESS AT WELL LOCATION \_\_\_\_\_  
MAILING ADDRESS Round Mt. Nevada

2. LOCATION NW 1/4 NW 1/4 Sec. 2 T. 10 N/S R. 43 E NVE County \_\_\_\_\_

PERMIT NO. 46687 & 46219  
Issued by Water Resources Parcel No. \_\_\_\_\_ Subdivision Name \_\_\_\_\_

3. TYPE OF WORK		4. PROPOSED USE			5. TYPE WELL	
New Well <input checked="" type="checkbox"/>	Recondition <input type="checkbox"/>	Domestic <input type="checkbox"/>	Irrigation <input checked="" type="checkbox"/>	Test <input type="checkbox"/>	Cable <input type="checkbox"/>	Rotary <input checked="" type="checkbox"/>
Deepen <input type="checkbox"/>	Other <input type="checkbox"/>	Municipal <input type="checkbox"/>	Industrial <input type="checkbox"/>	Stock <input type="checkbox"/>	Other <input type="checkbox"/>	

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
SANDY CLAY		0	13	13
DECOMPOSED QUARTZ W/LG.				
GRAVEL		13	20	7
HD. SANDY BR. CLAY		20	30	10
DECOMPOSED GRANIT W/S				
BR. CLAY		30	65	35
DECOMPOSED GRANIT W/LG.				
GRAVEL		65	70	5
SANDY BR. CLAY		70	80	10
DECOMPOSED GRANIT W/LG.				
GRAVEL		80	85	5
DECOMPOSED GRANIT W/S				
CLAY		85	115	30
DECOMPOSED GRANIT W/S				
SMALL GRAVEL		115	125	10
DECOMPOSED GRANIT W/LG.				
GRAVEL		125	140	15
SANDY BR. CLAY W/DECOMPOSED				
GRANIT STRINGERS		140	180	40
DECOMPOSED GRANIT W/LG.				
GRAVEL		180	185	5
HD. SANDY BR. CLAY		185	235	50
DECOMPOSED GRANIT W/GRAVEL		235	255	20
SANDY BR. CLAY		255	265	10
DECOMPOSED GRANIT & GRAVEL		265	270	5
SANDY BR. CLAY		270	295	25
DECOMPOSED GRANIT & GRAVEL		295	305	10
BR. CLAY W/d.g. STRINGERS		305	360	55
Date started.....	<u>8-24-84</u>			19.....
Date completed.....	<u>8-31-84</u>			19.....

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump
	<u>2563</u>	<u>131</u>	<u>8</u>

BAILER TEST

G.P.M. ....	Draw down.....feet	.....hours
G.P.M. ....	Draw down.....feet	.....hours
G.P.M. ....	Draw down.....feet	.....hours

8. WELL CONSTRUCTION

Diameter hole 24 inches Total depth 360 feet  
Casing record 16  
Weight per foot \_\_\_\_\_ Thickness 1/8  
Diameter From To  
16" Blank inches 0 feet 168 feet  
16" PERF inches 168 feet 360 feet  
\_\_\_\_ inches \_\_\_\_\_ feet \_\_\_\_\_ feet  
Surface seal: Yes  No  Type concrete  
Depth of seal 50 feet  
Gravel packed: Yes  No   
Gravel packed from 50 feet to 360 feet  
Perforations: 3  
Type perforation ROSCOE MOSS SHUTTER SCREEN  
Size perforation 1/8  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
From \_\_\_\_\_ feet to \_\_\_\_\_ feet

9. WATER LEVEL

Static water level 55 feet below land surface  
Flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
Water temperature \_\_\_\_\_ ° F. Quality \_\_\_\_\_

10. DRILLERS CERTIFICATION

This well was drilled under my supervision and the report is true to the best of my knowledge.  
Name HUMBOLDT DRILLING & PUMP CO., INC.  
BOX 592, WINNEMUCCA, NEV 89445  
Address \_\_\_\_\_ Contractor \_\_\_\_\_  
Nevada contractor's license number 015234  
Nevada contractor's drillers number C-23  
Nevada driller's license number 795  
Actual Driller  
Signed Bud Ventura Contractor  
Date Sept 14 1984