WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

STATE OF NEVADA
**DIVISION OF WATER RESOURCES**

# WELL DRILLERS REPORT

**Please complete this form in its entirety**

OFFICE USE ONLY
Log No. 25928
Permit No.
Basin 666 - KELLY CREEK

PRINT OR TYPE ONLY

NOTICE OF INTENT NO. 6243

1. OWNER GOLDFIELD MINING
MAILING ADDRESS P.O. Box 2790
RENO, Nev 89505

ADDRESS AT WELL LOCATION

2. LOCATION ~~SE SW~~ ¼ ~~SE SW~~ ¼ Sec ~~30~~ 32 T. 39 N/S R. 43 E HUMBOLDT County
PERMIT NO. 49152 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. TYPE OF WORK
New Well ☒ Recondition ☐
Deepen ☐ Other ☐

4. PROPOSED USE
Domestic ☐ Irrigation ☐ Test ☐
Municipal ☐ Industrial ☒ Stock ☐

5. TYPE WELL
Cable ☐ Rotary ☒
Other ☐ REVERSE

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| SANDY TOP SOIL | | 0 | 10 | 10 |
| SAND & COURSE GRAVEL | | 10 | 18 | 8 |
| HD.BR.CLAY W/COURSE SAND & | | | | |
| GRAVEL STRINGERS | | 18 | 113 | 95 |
| SMALL GRAVEL W/s SAND | | 113 | 118 | 5 |
| HD.BR.CLAY W/S SAND & | GRAVEL | | | |
| STRINGERS | | 118 | 138 | 20 |
| HD/BR.CLAY W/s SAND | | 138 | 155 | 17 |
| HD.BR.CLAY W/s SAND & | GRAVEL | | | |
| stringers | | 155 | 215 | 61 |
| GRAVEL W/S CLAY | | 215 | 230 | 15 |
| HD.CEMENTED GRAVEL | | 230 | 233 | 3 |
| GRAVEL W/S CLAY | | 233 | 240 | 7 |
| GRAVEL | | 240 | 295 | 55 |
| CLAY W/S GRAVEL | | 295 | 302 | 7 |
| GRAVEL & SAND | | 302 | 360 | 58 |
| HD SANDY BR.CLAY W/S | GRAVEL | | | |
| IMBEDED | | 360 | 424 | 64 |

Date started 12-12-85, 19
Date completed 12-19-85, 19

7. WELL TEST DATA

| Pump RPM | G.P.M. | Draw Down | After Hours Pump |
|---|---|---|---|
| | | | |

BAILER TEST
G.P.M. Draw down feet hours
G.P.M. Draw down feet hours
G.P.M. Draw down feet hours

8. WELL CONSTRUCTION
Diameter hole 18 inches Total depth 424 feet
Casing record 12
Weight per foot Thickness ¼

| Diameter | From | To |
|---|---|---|
| 12" BLANK inches | 0 feet | 104 feet |
| 12" PERF inches | 104 feet | 416 feet |
| 12" BLANK inches | 416 feet | 424 feet |
| inches | feet | feet |
| inches | feet | feet |
| inches | feet | feet |

Surface seal: Yes ☒ No ☐ Type concrete
Depth of seal 50 feet
Gravel packed: Yes ☒ No ☐
Gravel packed from 50 feet to 424 feet

Perforations:
Type perforation ROSCOE MOSS SHUTTER SCREEN
Size perforation 1/8
From feet to feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

9. WATER LEVEL
Static water level feet below land surface
Flow G.P.M. P.S.I.
Water temperature ° F. Quality

10. DRILLERS CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name HUMBOLDT DRILLING & PUMP CO., INC. (Contractor)
Address BOX 592, WINNEMUCCA, NEV 89445 (Contractor)
Nevada contractor's license number 015234
Nevada contractor's drillers number C-23
Nevada driller's license number 1448
Signed [signature] (Actual Driller) (Contractor)
Date 1-6-86

USE ADDITIONAL SHEETS IF NECESSARY

(Rev. 6-81) O-627 CR434