WELL LOG AND REPORT TO THE STATE ENGINEER OF NEVADA

Log No. 2704
Rec. 7/22 1954
Well No.
Permit No. 15124
Do not write in

Owner Sgt. Joe LaVoie Driller S.R.McKinney & Son

Address Box 186, Route 1, Paradise Valley Address 1042 S. Main L.V.N. Lic. No. 45

Location of well: SW ¼ NE ¼ Sec. 34, T. 21 N/S, R. 61 E, in Clark County

or

Water will be used for Domestic use Total depth of well 240'

Size of drilled hole 12"to100'10"to125'8"to240' Weight of casing per linear foot 8 guage

Thickness of casing 8 guage Temp. of water

Diameter and length of casing 8" I.D.to 150'
(Casing 12" in diameter and under give inside diameter; casing 12" in diameter give outside diameter.)

If flowing well give flow in c.f.s. or g.p.m. and pressure

If nonflowing well give depth of standing water from surface Surfuce

If flowing well describe control works
(Type and size of valve, etc.)

Date of commencement of well July-1, 54 Date of completion of well July-9, 54

Type of well rig Bucyruse Ere 24 L, Spudder

LOG OF FORMATIONS

From feet	To feet	Thickness feet	Type of material
0	1	1	brown clay
1	3	2	caliche
3	9	6	red sandy clay
9	16	7	caliche
16	23	7	~~XXXXXXX~~ red sandy clay
23	29	6	caliche, water
29	50	21	red sandy, cavy
50	70	20	red sandy clay
70	73	3	red sand stone, water
73	96	23	red sandy clay
96	101	5	red sand water
101	120	19	red sandy clay
120	132	12	red sandy clay
132	134	2	red sandstone water
134	145	11	red sand and gravel
145	164	19	red sandy clay
164	168	4	red sandstone water
168	186	18	red sandy clay
186	191	5	red sandstone water
191	215	24	red clay
215	231	16	red sand water
231	239	8	red sand with thin layers
239	240	1	of sandstone with water
239	240	1	gravel water

(OVER)

Water-bearing Formation, Casing Perforations, Etc.

Chief aquifer (water-bearing formation)

from 215 to 240 ft.

Other aquifers 186 to 191
164 to 168
132 to 145

First water at 23 feet.

Casing perforated

from to ft.

Size of perforations

919

LOG OF FORMATIONS—*Continued*

From feet	To feet	Thickness	Type of material

CASING RECORD

Diam. casing	From feet	To feet	Length	"Remarks"—Seals, Grouting, Etc.
8"I.D.	0	150	150	Cemented down to 100' 4yards of concrete

GENERAL INFORMATION—Pumping Test, Quality of Water, Etc.

Bailed 35 gal. from 35'

WELL DRILLER'S STATEMENT

This well was drilled under my jurisdiction and the above information is true to my best information and belief.

Signed J. R. McKinney & Son
Well Driller

By M. C. McKinney

License No. 45

Dated July 22, 19 54

(Not to be filled in by Driller)