

OFFICE USE ONLY  
Log No. 31291  
Permit No. \_\_\_\_\_  
Basin \_\_\_\_\_  
10989

~~1117~~ MW17  
PRINT OR TYPE ONLY

WELL DRILLER'S REPORT  
Please complete this form in its entirety

NOTICE OF INTENT NO. 10989

1. OWNER Woodward Clyde Consult ADDRESS AT WELL LOCATION Winecup Ranch  
MAILING ADDRESS 500 12th St Suite 100  
Oakland Calif.

2. LOCATION S E 1/4 NE 1/4 Sec. 35 T. 41 N/S R. 65 E. Elko County  
PERMIT NO. #22681 waiver M/D-119 Issued by Water Resources Parcel No. \_\_\_\_\_ Subdivision Name \_\_\_\_\_

3. TYPE OF WORK  
New Well  Recondition   
Deepen  Other

4. PROPOSED USE  
Domestic  Irrigation  Test   
Municipal  Industrial  Stock

5. TYPE WELL  
Cable  Rotary   
Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
clay & gravels		0	5	
cons. gravels & sand		5	20	
cons. coarse to fine gravels		20	40	
soft clay & fine gravels		40	60	
cons. gravel		60	70	
coarse gravel water		70	80	
layers brown sand & clay		80	100	
soft cons. gravel & sand		100	140	
gravels sand layers brown sand		140	190	
brown sand & clay		190	215	
la. gravel cons.		215	220	
gravels & sand		220	225	
cons. gravels		225	230	
cons. sand & clay layers		230	240	
very soft sand & clay		240	283	
cons. gravels - (HARDER)		283	290	
sticky bi. clay		290	410	
Hard cons. gravel		410	414	
sticky clay w/ thin gravel		414	474	
hard cons. gravels		474	480	
ht. tent brown clay sticky		480	500	
Hard cons. of		500	502	
sticky clay (brown)		502	650	

8. WELL CONSTRUCTION  
Diameter 2 1/2" PVC inches Total depth 650 feet  
sch 80 inches  
sch 80 inches

Casing record 2" PVC sch 80 with 3'  
Weight per foot \_\_\_\_\_ Thickness steel casing  
Diameter \_\_\_\_\_ From \_\_\_\_\_ Thickness from 0-3'

Surface seal: Yes  No  Type Cement  
Depth of seal 0-50 feet

Gravel packed: Yes  No   
Gravel packed from 50 feet to 260 feet

Perforations:  
Type perforation Reaper Moss  
Size perforation mill factory  
.0021  
From 240 feet to 260 feet

Date started 2/1 1989  
Date completed 2/14 1989

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump

BAILER TEST

G.P.M.	Draw down	feet	hours

9. WATER LEVEL  
Static water level 41 ft feet below land surface  
Flow 0 G.P.M. 0 P.S.I.  
Water temperature 0 °F Quality 0

10. DRILLER'S CERTIFICATION  
This well was drilled under my supervision and the report is true to the best of my knowledge  
Name RD Reynolds Drilling Contractor  
Address PO Box 402 Contractor  
Nevada contractor's license number issued by the State Contractor's Board 014410  
Nevada contractor's driller's number issued by the Division of Water Resources 1390  
Nevada driller's license number issued by the Division of Water Resources the on-site driller 1585  
Signed Russell T. Baly By driller performing actual drilling on site or contractor  
Date 2/25/89