

OFFICE USE ONLY  
 Log No. 31875  
 Permit No. 48664  
 Basin 10-121A Soda Sp. V. East

**WELL DRILLER'S REPORT**

PRINT OR TYPE ONLY

Please complete this form in its entirety

NOTICE OF INTENT NO. 10200

1. OWNER CORONA GOLD INC. ADDRESS AT WELL LOCATION SANTA FE MINE  
MAILING ADDRESS/O HYDRO-SEARCH INC. SANTA FE MINE  
5250 S. VIRGINIA ST. # 280, RENO, NV. 89502 NE LUNING  
 2. LOCATION SW 1/4 SW 1/4 Sec. 31 T. 9 (N/S R. 35 E. MINERAL County  
 PERMIT NO. 48664 Issued by Water Resources Parcel No. Subdivision Name

3. TYPE OF WORK  
 New Well  Recondition   
 Deepen  Other   
 4. PROPOSED USE PW#3  
 Domestic  Irrigation  Test   
 Municipal  Industrial  Stock  Other   
 5. TYPE WELL  
 Cable  Rotary   
 Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Course sand, gravel clay		0	100	100
Large grave, sand & clay		100	160	60
Sand & clay		160	900	740
Fine gravel, sand & clay		900	940	40
Clay & sand		940	1000	60
Fine gravel & clay mix		1000	1040	40
White & brown sticky clay, broken rock		1040	1100	60
Clay & broken rock		1100	1260	160
White-brown clay, broken rock		1260	1302	42

8. WELL CONSTRUCTION  
 Diameter 17-1/2 inches Total depth 1302 feet  
 Casing record 12-3/4 inch O.D. x 1/4 inch wall  
 Weight per foot 33.38 Thickness  
 Conductor:  

Diameter	From	To
24-20 inches	+2 feet	58 feet
12 inches	+2 feet	1302 feet

 Surface seal: Yes  No  Type cement sand grout  
 Depth of seal 58 feet  
 Gravel packed: Yes  No   
 Gravel packed from surface feet to 1302 feet  
 Wadsworth 3/8 inch minus well rock  
 Perforations: 12 inch wire wrap screen .080" slot  
 Type perforation Extra heavy construction  
 Size perforation Milled 3 inch x 1/8 inch Dbl. Std.  
 From Perf. 1002-1062 feet to Scm 1222-1242 feet  
 From Scm 1062-1082 feet to Perf. 1242-1282 feet  
 From Perf. 1082-1122 feet to Scm 1282-1302 feet  
 From Scm 1122-1202 feet to \_\_\_\_\_ feet  
 From Perf. 1202-1222 feet to \_\_\_\_\_ feet

Date started April 24, 1989  
 Date completed May 10, 1989

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	Water Head	Pump
		<u>7-10'</u>		<u>06</u>

9. WATER LEVEL  
 Static water level 865 feet below land surface  
 Flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature 7.9 °F Quality good

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name SARGENT IRRIGATION COMPANY  
 Address 9955 N. VIRGINIA ST., RENO, NV. 89506  
 Nevada contractor's license number issued by the State Contractor's Board 21246  
 Nevada contractor's driller's number issued by the Division of Water Resources 1391  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1388/1491  
 Signed [Signature]  
 By driller performing actual drilling on site or contractor  
 Date JULY 14, 1989

BAILER TEST

G.P.M.	Draw down	feet	hours

**WELL DRILLER'S REPORT**

PRINT OR TYPE ONLY

Please complete this form in its entirety

NOTICE OF INTENT NO. 10200

**REVISED**

1. OWNER CORONA GOLD INC. ADDRESS AT WELL LOCATION SANTA FE MINE  
 MAILING ADDRESS C/O HYDRO SEARCH INC. NE LUNING  
5250 S. VIRGINIA ST. #280, RENO, NV. 89502  
 2. LOCATION SW 1/4 SW 1/4 Sec. 31 T. 9 N. R. 35 E. MINERAL County  
 PERMIT NO. 48664 Issued by Water Resources Parcel No. Subdivision Name

3. TYPE OF WORK  
 New Well  Recondition   
 Deepen  Other   
 4. PROPOSED USE PW#3  
 Domestic  Irrigation  Test   
 Municipal  Industrial  Stock   
 5. TYPE WELL  
 Cable  Rotary   
 Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Course sand, gravel & clay		0	100	100
Large gravel, sand & clay		100	160	60
Sand & clay		160	900	740
Fine gravel, sand & clay		900	940	40
Clay & sand		940	1000	60
Fine gravel & clay mix		1000	1040	40
White & brown sticky clay, broken rock		1040	1100	60
Clay & broken rock		1100	1260	160
White-brown clay, broken rock		1260	1302	42

8. WELL CONSTRUCTION  
 Diameter 17-1/2 inches Total depth 1302 feet  
 Casing record 12-3/4 inch O.D. X 1/4 inch wall  
 Weight per foot 33.38 Thickness  

Diameter	From	To
<u>24-20</u> inches	<u>+2</u> feet	<u>58</u> feet
<u>12</u> inches	<u>+2</u> feet	<u>1302</u> feet

 Surface seal: Yes  No  Type cement sand grout  
 Depth of seal 58 feet  
 Gravel packed: Yes  No   
 Gravel packed from surface feet to 1302 feet  
 Wadsworth 3/8 inch minus well rock  
 Perforations: 12 inch wire wrap screen .080  
 Type perforation Extra Heavy construction  
 Size perforation Milled 3 inch x 1/8 inch Dbl Std. Sp  
 From Perf. 1002-1062 feet to Scrn. 1222-1242 feet  
 From Scrn. 1062-1082 feet to Perf. 1242-1282 feet  
 From Perf. 1082-1122 feet to Scrn. 1282-1302 feet  
 From Scrn. 1122-1202 feet to \_\_\_\_\_ feet  
 From Perf. 1202-1222 feet to \_\_\_\_\_ feet

Date started April 24, 1989  
 Date completed May 5, 1989

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump
	<u>100</u>	<u>200</u>	<u>72</u>

BAILER TEST  
 G.P.M. Draw down \_\_\_\_\_ feet \_\_\_\_\_ hours  
 G.P.M. Draw down \_\_\_\_\_ feet \_\_\_\_\_ hours  
 G.P.M. Draw down \_\_\_\_\_ feet \_\_\_\_\_ hours

9. WATER LEVEL  
 Static water level 865 feet below land surface  
 Flow \_\_\_\_\_ G.P.M. \_\_\_\_\_ P.S.I.  
 Water temperature 79 °F Quality Good

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name SARGENT IRRIGATION COMPANY  
 Address 9955 N. VIRGINIA ST., RENO, NV. 89506  
 Nevada contractor's license number 21246  
 issued by the State Contractor's Board  
 Nevada contractor's driller's number 1391  
 issued by the Division of Water Resources  
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1388/1491  
 Signed [Signature]  
 By driller performing actual drilling on site or contractor  
 Date JULY 21, 1989