WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety

OFFICE USE ONLY
Log No. 34172
Permit No.
Basin 8-105

PRINT OR TYPE ONLY

NOTICE OF INTENT NO. 4506

1. OWNER Greg Gumble
MAILING ADDRESS 1650 Stephanie Lane
Minden, Nevada 89423

ADDRESS AT WELL LOCATION 2820 Esaw
Minden, Nevada 89423

2. LOCATION NW ¼ NW ¼ Sec. 35 T. 14 N/S R. 20 E. Douglas County
PERMIT NO. (Issued by Water Resources) 21-240-36 (Parcel No.) Johnson Lane (Subdivision Name)

3. TYPE OF WORK
New Well ☒ Recondition ☐
Deepen ☐ Other ☐

4. PROPOSED USE
Domestic ☒ Irrigation ☐ Test ☐
Municipal ☐ Industrial ☐ Stock ☐

5. TYPE WELL
Cable ☐ Rotary ☒
Other ☐ Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Overburden with blow sand		0	6	6
Sandstone, tight, hard, light colored		6	55	49
Clay seams, tight		55	98	44
Volcanic materials, medium hard, red to black color		98	140	42
Clay seams, tight, tan colored		140	200	60
Fractured rock with conglomerates carrying water	xx	200	235	35
Clay, tight		235	240	5
Total depth: 240 feet				

Date started Sept 4, 1990
Date completed Sept 7, 1990

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump
Flushed well with clean water to remove drill mud and to intalll gravel for gravel pack. Blew well with 250 psi air to develop well. Blew 10-12 gpm for 3 hours from 220ft.			

BAILER TEST
G.P.M. ..... Draw down ..... feet ..... hours
G.P.M. ..... Draw down ..... feet ..... hours
G.P.M. ..... Draw down ..... feet ..... hours

8. WELL CONSTRUCTION
Diameter 11 3/4 inches Total depth 240 feet
8 3/4 inches
inches
Casing record Steel 6 5/8" OD
Weight per foot 13.03 Thickness .188

Diameter	From	To
6 5/8 inches	2 feet	240 feet
inches	feet	feet
inches	feet	feet
inches	feet	feet
inches	feet	feet
inches	feet	feet

Surface seal: Yes ☒ No ☐ Type Concrete
Depth of seal 60 feet
Gravel packed: Yes ☒ No ☐
Gravel packed from 60 feet to 240 feet

Perforations:
Type perforation Factory mill slotted
Size perforation 3" x 3/32"
From 210 feet to 230 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

9. WATER LEVEL
Static water level 137 feet below land surface
Flow 10 - 12 G.P.M. P.S.I.
Water temperature cool °F Quality good

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name A & H PUMP CO. (Contractor)
Address Carson City, Nv 89701 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 23295
Nevada contractor's driller's number issued by the Division of Water Resources
Nevada driller's license number issued by the Division of Water Resources, the on-site driller
Signed (By driller performing actual drilling on site or contractor)
Date

(Rev. 11-85) USE ADDITIONAL SHEETS IF NECESSARY (O) 627