


HUMBOLDT DRILLING & PUMP CO., INC.

P.O. BOX 592
4675 W. WINNEMUCCA BLVD.
WINNEMUCCA, NEVADA, 89445
(702) 623-5259

Log# 34361
Permit# W-194
Basin 9-108



Mr. George Ball
Waterresource
730 Tahoe Street
Reno, Nevada 89509

RE: Mayson Valley-Dept. of Wildlife
Well Abandonment

August 27, 1986

#2 Holes
@ Location
of (#3) 6" TEST WELL

SE 1/4 NW 1/4 Section 18, T. 14 N., R. 26 E.

Dear George:

Well was drilled to 535 ft. (total depth) with 12" bit. Elog was run and 400 ft. of double row 6" perf pipe and 20 ft. of 6" blank dropped to the bottom of the hole. An internal hook was used to pull 80,000 lbs., with no success. The tool pulled out of the 6" pipe.

At this time we decided to abandon the well. The first step was to run tools inside the pipe to 480 ft. Drilling mud was at 45-50 viscosity at the time of the drop. Cement grout was pumped down the well to 12 ft. from the surface. The balance of the hole was filled with clay.

The above mentioned procedure was supervised by driller Norm Parsons.

C.I.R.C. DID NOT FREE UP
CASING - BACKFILLED W/
CUTTINGS TO 60' - THEN
CEMENTED TO 12' (G.L.)

#1454
Respectfully Submitted,

Brad L. Santucci
Drilling Division

OK - PSR TELECON
BLS:tt w/ GARY TOMPKINS @ Humboldt

cc: Dept of Wildlife

8500 80 TRG