WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY
#3

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety

OFFICE USE ONLY
Log No. 35362
Permit No.
Basin 212

PRINT OR TYPE ONLY

NOTICE OF INTENT NO. 4149

1. OWNER Texaco/Earthfax Engineering
MAILING ADDRESS 7324 So. 1300 E. Ste.100
Midvale, Utah 84047

ADDRESS AT WELL LOCATION

2. LOCATION NE ¼ SE ¼ Sec. 33 T. 19 ~~N~~ S R. 62 E. Clark County
PERMIT NO. (Issued by Water Resources) Parcel No. Subdivision Name

3. TYPE OF WORK
New Well ☒ Recondition ☐
Deepen ☐ Other ☐

4. PROPOSED USE Monitoring
Domestic ☐ Irrigation ☐ Test ☐
Municipal ☐ Industrial ☐ Stock ☐

5. TYPE WELL
Cable ☐ Rotary ☒
Other ☐

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Fill material		0	2	2
Moist sandy silt		2	12	10
Moist silty clay		12	15	3
Cem. silty sand, minor clay		15	21	6
Sand		21	28	7
Sand w/calliche, minor clay		28	34	6
Moist silty clay		34	38	4
Bamp sillty sand		38	42	4
Caliche		42	44	2
Silty sand, some cem.		44	57	13
Moist clayey silt		57	63	6
Dry silty sand		63	65	2
(No returns)		65	70	5
Cem. silty sand		70	84	14
Cem. sand w/ caliche		84	92	8
Cem. clayey silt, some cal.		92	101	9
Moist silty clay, occ. cal.		101	109	8
Cem. silt with clay		109	120	11

RECEIVED
JUN 17 1991
Div. of Water Resources
Branch Office - Las Vegas, NV

Date started November 12, 19 90
Date completed November 20, 19 90

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump

BAILER TEST
G.P.M. ..... Draw down ..... feet ..... hours
G.P.M. ..... Draw down ..... feet ..... hours
G.P.M. ..... Draw down ..... feet ..... hours

8. WELL CONSTRUCTION
Diameter 8 inches Total depth 120 feet
inches
inches
Casing record PVC
Weight per foot ..... Thickness Sched. 40

Diameter	From	To
4 inches	+1 feet	120 feet
inches	feet	feet
inches	feet	feet
inches	feet	feet
inches	feet	feet
inches	feet	feet

Surface seal: Yes ☒ No ☐ Type Cement
Depth of seal 72 feet
Gravel packed: Yes ☐ No ☒ Sand packed
~~Gravel~~ packed from 72 feet to 120 feet

Perforations:
Type perforation
Size perforation 0.010 Slotted PVC screen
From 80 feet to 120 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

9. WATER LEVEL
Static water level 91 feet below land surface
Flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name THOMPSON DRILLING CO., INC. Contractor
Address 4185 W. Harmon Llas Vegas, NV 89103 Contractor
Nevada contractor's license number issued by the State Contractor's Board 4286A
Nevada contractor's driller's number issued by the Division of Water Resources 290
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1686
Signed Richard Thompson
By driller performing actual drilling on site or contractor
Date May 15, 1991

(Rev. 11-85) USE ADDITIONAL SHEETS IF NECESSARY (O)-627