WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 35823
Permit No.
Basin 8-104

NOTICE OF INTENT NO.

1. OWNER CAPITAL BEVERAGE
MAILING ADDRESS 2333 FAIRVIEW DRIVE
CARSON CITY, NEVADA 89701

ADDRESS AT WELL LOCATION 2333 FAIRVIEW DRIVE
CARSON CITY, NEVADA 89701

2. LOCATION NW ¼ SE ¼ Sec. 21 T. 15 N XXR 20 E. CARSON CITY County
PERMIT NO. M/O-3661 (Issued by Water Resources) | N/A (Parcel No.) | N/A (Subdivision Name)

3. WORK PERFORMED
[XX] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[ ] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [XX] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [XX] Rotary [ ] RVC
[ ] Air [ ] Other

6. LITHOLOGIC LOG MW-3

Material	Water Strata	From	To	Thickness
ASPHALTIC CONCRETE OVER A GGREGATE BASE		0.0	1.0	1.0
RED BROWN SILTY SAND		1.0	4.5	3.5
LIGHT BROWN SILTY SAND		4.5	10.0	5.5
WHITE TO LIGHT BROWN SAND		10.0	11.0	1.0
WHITE TO LIGHT BROWN SILTY SAND		11.0	15.0	4.0
LIGHT BROWN SAND		15.0	21.0	6.0
BROWN SILTY SAND		21.0	29.5	8.5
RED BROWN SAND		29.5	32.0	2.5
BROWN CLAYEY SAND		32.0	39.0	7.0
BROWN SILTY SAND		39.0	47.5	8.5
WHITE TO LIGHT BROWN SAND		47.5	48.5	1.0
RED BROWN SILTY SAND		48.5	55.0	

Date started FEBRUARY 5, 1991
Date completed FEBRUARY 6, 1991

7. WELL TEST DATA
~~TEST METHOD~~: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

-NOTE- Well removed by excavation Late March 1991 (soil removal remediation)

8. WELL CONSTRUCTION
Depth Drilled 55.0 Feet Depth Cased 55.0 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
8.0 Inches		0.0 Feet	55.0 Feet
Inches		Feet	Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
2.0	0.5	SCHEDULE 40	0.0	55.0

Perforations:
Type perforation SLOTTED
Size perforation 0.010 INCHES
From 45.0 feet to 55.0 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 40.5
Placement Method: [ ] Pumped [X] Poured
Seal Type: [ ] Neat Cement [ ] Cement Grout [XX] Concrete Grout

Gravel Packed: [XX] Yes [ ] No
From 43.0 feet to 55.0 feet

9. WATER LEVEL
Static water level 45.0 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name PEZONELLA ASSOCIATES (Contractor)
Address 520 EDISON WAY RENO, NEVADA 89502 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board C-4186
Nevada driller's license number issued by the Division of Water Resources, the on-site driller M-1688
Signed (By driller performing actual drilling on site or contractor)
Date 5/30/91 Raymond M. Pezonella

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627