WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

SECTION 33 ACCD

PRINT OR TYPE ONLY

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety

OFFICE USE ONLY
Log No. 36076
Permit No.
Basin 8-105

NOTICE OF INTENT NO. 13649

1. OWNER City of Carson
MAILING ADDRESS 3300 Butti Way
Carson City, NV 89701

ADDRESS AT WELL LOCATION City Well
WAIVER # W-314

2. LOCATION ~~SE~~ SW ¼ ~~NW~~ NE ¼ Sec. 33 T. 15 N/S R. 20 E. Douglas County

PERMIT NO. ~~51747~~ 53141, 53142 (Issued by Water Resources) | Parcel No. | Subdivision Name

3. TYPE OF WORK
New Well [X] Recondition [ ]
Deepen [ ] Other [ ]

4. PROPOSED USE Monitor
Domestic [ ] Irrigation [ ] Test [ ]
Municipal [ ] Industrial [ ] Stock [ ]

5. TYPE WELL
Cable [ ] Rotary [X]
Other [ ]

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Coarse Sand & Gravel		0	13	13
Decomposed Granite		13	90	77
Decomposed Granite w/s trace of Clay		90	510	420
Decomposed Granite w/s Boulders & Clay		510	520	10

Date started 11/15, 19 89
Date completed 11/21, 19 89

7. WELL TEST DATA

Pump RPM	G.P.M.	Draw Down	After Hours Pump

BAILER TEST
G.P.M. ..... Draw down ..... feet ..... hours
G.P.M. ..... Draw down ..... feet ..... hours
G.P.M. ..... Draw down ..... feet ..... hours

8. WELL CONSTRUCTION
Diameter 10 inches Total depth 520 feet
..... inches
..... inches
Casing record 4" PVC
Weight per foot ..... Thickness SCH 80

Diameter	From	To
4" Steel Blank	+2 feet	8 feet
4" SCH 80-PVC Blank	8 feet	298 feet
4" SCH 80-PVC Perf	298 feet	318 feet
4" SCH 80-PVC Blank	318 feet	358 feet
4" SCH 80-PVC Perf	358 feet	378 feet
4" SCH 80-PVC Blank	378 feet	418 feet

Surface seal: Yes [X] No [ ] Type Concrete
Depth of seal 55 feet
Gravel packed: Yes [X] No [ ]
Gravel packed from 55 feet to 510 feet

Perforations:
Type perforation
Size perforation
From 4" SCH 80 PVC Perf 418 feet to 438 feet
From 4" SCH 80 PVC Blank 438 feet to 478 feet
From 4" SCH 80 PVC Perf 478 feet to 498 feet
From 4" SCH 80 PVC Blank 498 feet to 508 feet
From Concrete Plug 508 feet to 510 feet

9. WATER LEVEL
Static water level 115' feet below land surface
Flow ..... G.P.M. ..... P.S.I.
Water temperature ..... °F Quality .....

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Humboldt Drilling & Pump Co., Inc. (Contractor)
Address P.O. Box 592, Winnemucca NV 89445 (Contractor)
Nevada contractor's license number issued by the State Contractor's Board 015234
Nevada contractor's driller's number issued by the Division of Water Resources C-8323
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 795
Signed ..... (By driller performing actual drilling on site or contractor)
Date 2-21-90

(Rev. 11-85) USE ADDITIONAL SHEETS IF NECESSARY (O)-627