WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 37059
Permit No.
Basin 91

NOTICE OF INTENT NO. 17570

1. OWNER NORM ORCUTT/RAYMOND J. PONCIA JR
MAILING ADDRESS 7090 Aspen Glen Road
Reno, NV 89509

ADDRESS AT WELL LOCATION
635 ~~Lot #3~~ Riverdale Cir.
Verdi, NV. 89439

2. LOCATION ~~SE~~ ¼ NE ~~SE~~ ¼ Sec. 7 T. 19N N/S R. 18 E. Washoe County
PERMIT NO. (Issued by Water Resources) 38-294-06 (Parcel No.) Riverdale Sub Division Lot 3 Blk D (Subdivision Name)

3. WORK PERFORMED
[X] New Well [ ] Replace [ ] Recondition
[ ] Deepen [ ] Abandon [ ] Other

4. PROPOSED USE
[X] Domestic [ ] Irrigation [ ] Test
[ ] Municipal/Industrial [ ] Monitor [ ] Stock

5. WELL TYPE
[ ] Cable [X] Rotary [ ] RVC
[X] Air [ ] Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Top soil		0	1	1
Boulders & gravel with sand, some clays		1	10	9
Brown sand		10	16	6
Granite boulder		16	29	13
Boulder & gravel with brown clay		29	46	17
GRay clay with small boulders		46	106	60
Dark gray clay		106	166	60
Harder volcanic rock with clay streaks		166	199	33
Gray clay		199	221	22
Soft zone	X	221	223	2
Gray clay, sandy		223	261	38
Soft zone	X	261	265	4
Gray clay		265	275	10

Date started 6-19-91, 19
Date completed 6-21-91, 19

7. WELL TEST DATA
TEST METHOD: [ ] Bailer [ ] Pump [ ] Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 275 Feet Depth Cased 275 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
10 Inches	0 Feet	100 Feet
8 5/8 Inches	100 Feet	200 Feet
Inches	Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.92	.188	0	275

Perforations:
Type perforation factory sawed slot
Size perforation 3/32 x 3 x 5 around
From 210 feet to 230 feet
From 250 feet to 270 feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: [X] Yes [ ] No
Depth of Seal 100 ft.
Placement Method: [X] Pumped [ ] Poured
Seal Type: [ ] Neat Cement [X] Cement Grout [ ] Concrete Grout

Gravel Packed: [X] Yes [ ] No
From 100 feet to 275 feet

9. WATER LEVEL
Static water level 44 feet below land surface
Artesian flow 13 G.P.M. P.S.I.
Water temperature cold °F Quality clear

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Wayne Drilling, Inc. (Contractor)
Address P.O. Box 12370 (Contractor)
Reno, NV 89510
Nevada contractor's license number issued by the State Contractor's Board 22549
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 923
Signed [signature] (By driller performing actual drilling on site or contractor)
Date June 24, 1991

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627