


OFFICE USE ONLY  
 Log No. 37294  
 Permit No. \_\_\_\_\_  
 Basin 6-87  


PRINT OR TYPE ONLY  
 DO NOT WRITE ON BACK

**WELL DRILLER'S REPORT**

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 12897

1. OWNER HARRAH'S AUTO COLLECTION ADDRESS AT WELL LOCATION \_\_\_\_\_  
 MAILING ADDRESS 10 Lake Street 1150 Icehouse Way  
Reno, NV 89501 Sparks, NV 89432

2. LOCATION SE 1/4 NE 1/4 Sec. 8 T. 19N N/S R. 20 E Washoe County  
 PERMIT NO. M/O-173 MW-3 Issued by Water Resources Parcel No. \_\_\_\_\_ Subdivision Name \_\_\_\_\_

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other \_\_\_\_\_

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other TUBEX

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Asphalt		0	6"	6"
Clayey gravel/ 60% fine (up to 1") sub-angular dark brown gravel, w/ 40% clay & silt		6"	3	2 1/2
Poorley graded gravel/ light brown coarse grained gravel, rounded to sub-rounded, average grain size 1-2", gravel consists predominately of volcanic clasts		3	8	5
Well graded gravel/ med brown, 80% gravel up to 8" in size, 10% fine sand, 10% silt		8	12	4
Well graded gravel w/ silt & sand/ Light brown sub-angular to rounded gravel (50%-55%), 30% coarse sand, 10%-15% silt		12	15	3
Poorley graded gravel/ loosely consolidated poorely graded gravel w/ 5% clay		15	19	4
Silty gravel/poorely graded gravel, sub-angular to sub-rounded, cobbles 4" w/30% silt		19	22	3
Poorley graded gravel w/clay/ very coarse gravel w/10% clay		22	24	19

8. WELL CONSTRUCTION  
 Depth Drilled 24 Feet Depth Cased 23.8 Feet

HOLE DIAMETER (BIT SIZE)  
 From 8" Inches 0 Feet 24 Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet  
 \_\_\_\_\_ Inches \_\_\_\_\_ Feet \_\_\_\_\_ Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4"		sch 40 PVC	0	23.8

Perforations:  
 Type perforation factory sawed slot  
 Size perforation .020 x 1 1/2 x 6 rows  
 From 13.8 feet to 23.8 feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet  
 From \_\_\_\_\_ feet to \_\_\_\_\_ feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 11.3' w/2' bentonite  Neat Cement  
 Placement Method:  Pumped 9.4'  Cement Grout  
 Poured  Concrete Grout

Gravel Packed:  Yes  No #3 Monterey Sand  
 From 11.3 feet to 23.8 feet

9. WATER LEVEL  
 Static water level 14 ft on 8-22-89 feet below land surface  
 Artesian flow not known G.P.M. \_\_\_\_\_ P.S.I. \_\_\_\_\_  
 Water temperature N/A °F Quality not known

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.  
 Name Wayne Drilling, Inc. Contractor  
 Address P.O. Box 12370, Reno, NV 89510 Contractor

7. Start 8-9-89 WELL TEST DATA Comp 1, 8-10-89

TEST METHOD:  Bailer  Pump  Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
Information recieved 10-13-91	K/J/C #882518.01	

Nevada contractor's license number 22549 issued by the State Contractor's Board.  
 Nevada driller's license number issued by the 908 Division of Water Resources, the on-site driller.  
 Signed Wayne Drilling, Inc. By driller performing actual drilling on site or contractor  
 Date November 5, 1991