WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 37308
Permit No.
Basin 091

NOTICE OF INTENT NO. 17324

1. OWNER: Chris Glover
MAILING ADDRESS: 1705 Greg St, Sparks, Nv 89431
ADDRESS AT WELL LOCATION: 300 Sylvan Cr

2. LOCATION: SE ¼ SE ¼ Sec. 7 T 19 N/S R 18 E Washoe County
PERMIT NO. — Issued by Water Resources
38-046-19 — Parcel No.
Verdi — Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☒ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☐ Air ☐ Other Mud

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
Overburden		0	4	4
Hard rock - broken clean white black yellow some red		4	64	60
Truckee formation		64	96	32
Gray clay with scattered cobbles		96	126	30
Black green gray rock medium hard		126	195	69
First water was 146' bore was drilled with air to 160' - very unstable - mudded-up to drill to a T.D. of 195'				
T.D. 195'				
There is a 20 ft blank on bottom of perf to aid in development and act as cellar.				

Date started 8/2/91, 19
Date completed 8/5/91, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)
	20+	2

8. WELL CONSTRUCTION
Depth Drilled 195 Feet Depth Cased 195 Feet

HOLE DIAMETER (BIT SIZE)

Inches	From (Feet)	To (Feet)
10	0	120
8	120	195

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
6 5/8	12.92	.188	+1½	195

Perforations:
Type perforation factory
Size perforation 3/32 X 3
From 155 feet to 175 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 115
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 115 feet to 195 feet

9. WATER LEVEL
Static water level 14 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature cold °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name Aqua Drilling & Well Service, Inc — Contractor
Address 625 Spice Islands Dr Suite L — Contractor
Sparks, Nv 89431
Nevada contractor's license number issued by the State Contractor's Board 15291
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1132
Signed Roger M. Thrall — By driller performing actual drilling on site or contractor
Date Roger M. Thrall 8/8/91

AUG 28 1991 STATE ENGINEER

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627