GQTW-6

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 37501
Permit No.
Basin 51

NOTICE OF INTENT NO. 16715

1. OWNER NEWMONT GOLD INC.
MAILING ADDRESS P.O. BOX 669
CARLIN, NV 89822-0669

ADDRESS AT WELL LOCATION
NEWMONT GOLD MINE

2. LOCATION NE ¼ SE ¼ Sec 34 T 34 N/S R 51 E EUREKA County
PERMIT NO. 56411-T (Issued by Water Resources) | N/A (Parcel No.) | N/A (Subdivision Name)

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE
☐ Domestic ☐ Irrigation ☐ Test
☒ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☐ Rotary ☒ RVC
☐ Air ☐ Other

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thickness
BROWN HARD ROCK		0	80	80
BROWN ROCK & CLAY		80	125	45
GRAY ROCK, HARD BLACK ROCK		125	215	90
HARD BLACK ROCK		215	265	40
FRACT GRAY ROCK		265	295	30
GRAY ROCK HARD		295	350	55
FRACT GRAY ROCK		350	430	80
GRAY ROCK & CLAY		430	520	90
GRAY ROCK		520	665	145
GRAY CLAY		665	685	20
GRAY ROCK & CLAY		685	710	25
GRAY ROCK		710	730	20
GRAY ROCK & CLAY		730	755	25
FRACT RED GRAY BROWN ROCK	X	755	775	20
GRAY ROCK		775	860	85
FRACT GRAY ROCK	X	860	885	20
GRAY ROCK		885	945	60
FRACT GRAY ROCK	X	945	960	15
GRAY ROCK		960	1020	60
BLACK & WHITE ROCK		1020	1035	15
GRAY ROCK		1035	1060	25
BLACK ROCK		1060	1100	40
BLACK & WHITE ROCK		1100	1190	90
BLACK ROCK		1190	1495	305
FRACT BLACK ROCK	X	1495	1550	55
BLACK ROCK		1550	1620	70

Date started 8-28, 19 91
Date completed 9-19, 19 91

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☐ Air Lift

G.P.M.	Draw Down (Feet Below Static)	Time (Hours)

8. WELL CONSTRUCTION
Depth Drilled 1620 Feet Depth Cased 1600 Feet

HOLE DIAMETER (BIT SIZE)

		From	To
35 Inches		0 Feet	37 Feet
22 Inches		37 Feet	1620 Feet
Inches		Feet	Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
30	118.65	.375	0	37
16	62.58	.375	+2	660
			1580	1600

Perforations:
Type perforation WIRE WRAP
Size perforation .125
From 660 feet to 1580 feet
From feet to feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 0-50
Placement Method: ☒ Pumped ☐ Poured
Seal Type: ☒ Neat Cement ☐ Cement Grout ☐ Concrete Grout

Gravel Packed: ☒ Yes ☐ No
From 580 feet to 1590 feet

9. WATER LEVEL
Static water level 530 feet below land surface
Artesian flow N/A G.P.M. N/A P.S.I.
Water temperature COOL °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name LANG EXPLORATORY DRILLING (Contractor)
Address 2286 W. 1500 S. (Contractor)
SALT LAKE CITY, UT 84104
Nevada contractor's license number issued by the State Contractor's Board 0021976
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1731
Signed [signature] (By driller performing actual drilling on site or contractor)
Date Oct. 19, 1991

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627