MW - 14

WHITE—DIVISION OF WATER RESOURCES
CANARY—CLIENT'S COPY
PINK—WELL DRILLER'S COPY

PRINT OR TYPE ONLY
DO NOT WRITE ON BACK

STATE OF NEVADA
DIVISION OF WATER RESOURCES

# WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

OFFICE USE ONLY
Log No. 37544
Permit No.
Basin 41-C

NOTICE OF INTENT NO. 20169

1. OWNER DEE GOLD MINING COMPANY
MAILING ADDRESS P. O. Box 1193
Elko, Nevada 89801

ADDRESS AT WELL LOCATION DEE GOLD MINING CO.
33 miles north of Carlin, Nevada
Carlin, Nevada 89822

2. LOCATION SE ¼ SW ¼ Sec. 10 T 36 N/S R 49 E Elko County
PERMIT NO. J-258 U/O-557 (Issued by Water Resources) Parcel No. Subdivision Name

3. WORK PERFORMED
☒ New Well ☐ Replace ☐ Recondition
☐ Deepen ☐ Abandon ☐ Other

4. PROPOSED USE Collection
☐ Domestic ☐ Irrigation ☐ Test
☐ Municipal/Industrial ☐ Monitor ☐ Stock

5. WELL TYPE
☐ Cable ☒ Rotary ☐ RVC
☒ Air ☐ Other

6. LITHOLOGIC LOG

| Material | Water Strata | From | To | Thickness |
|---|---|---|---|---|
| Boulders + Gravel | | 0 | 31' | |
| Damp Clay | | 31 | 90' | |
| Med Hard + Broken | | 90 | 130' | |
| Rock | | | | |
| Neat Cement | | 10' | 0' | |
| Hole Plug 3/8" | | 22 | 10' | |
| Fine Sand | | 60 | 22' | |
| Coarse Sand | | 120 | 60' | |

Date started 9-30-91, 19
Date completed 10-1-91, 19

7. WELL TEST DATA
TEST METHOD: ☐ Bailer ☐ Pump ☒ Air Lift

| G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|---|---|---|
| | | 3/4 Hr |

8. WELL CONSTRUCTION
Depth Drilled 130 Feet Depth Cased 120 Feet

HOLE DIAMETER (BIT SIZE)

| Inches | From (Feet) | To (Feet) |
|---|---|---|
| 10 5/8" | 0 | 130 |
| | | |
| | | |

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|---|---|---|---|---|
| 6" | PVC | Sec .140 | 0 | 30' |
| 6" | PVC | Screen .020 | 30 | 60' |
| 6" | PVC | " .040 | 60 | 120' |

Perforations:
Type perforation Horz Slot
Size perforation .040 & .020
From .040 120' feet to 60' feet
From .020 60' feet to 30' feet
From feet to feet
From feet to feet
From feet to feet

Surface Seal: ☒ Yes ☐ No
Depth of Seal 10'
Placement Method: ☐ Pumped ☒ Poured
Sand ~~Gravel~~ Packed: ☒ Yes ☐ No
From 120 feet to 30' feet

Seal Type:
☒ Neat Cement
☐ Cement Grout
☐ Concrete Grout

9. WATER LEVEL
Static water level 53.41 feet below land surface
Artesian flow G.P.M. P.S.I.
Water temperature °F Quality

10. DRILLER'S CERTIFICATION
This well was drilled under my supervision and the report is true to the best of my knowledge.
Name EKLUND DRILLING COMPANY, INC (Contractor)
Address P. O. Box 2786 (Contractor)
Elko, Nevada 89801
Nevada contractor's license number issued by the State Contractor's Board 0030823
Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1762
Signed Floyd H. Woodall (By driller performing actual drilling on site or contractor)
Date 10-14-91

STATE ENGINEER'S OFFICE '91 OCT 16 A11:03

(Rev. 3-91) USE ADDITIONAL SHEETS IF NECESSARY (O)-627