

WHITE-DIVISION OF WATER RESOURCES  
CANARY-CLIENT'S COPY  
PINK-WELL DRILLER'S COPY

STATE OF NEVADA  
DIVISION OF WATER RESOURCES

OFFICE USE ONLY  
Log No. 37864  
Permit No. 56977  
Basin 4-66

PRINT OR TYPE ONLY  
DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in  
accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 18291

1. OWNER PINSON MINING COMPANY ADDRESS AT WELL LOCATION PINSON MINE  
 MAILING ADDRESS P.O. BOX 129  
WINNEMUCCA, NV 89446

2. LOCATION NW 1/4 SW 1/4 Sec. 28 T 38 N 42 R. EUREKA County  
 PERMIT NO. W-355 N/A N/A  
Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED  
 New Well  Replace  Recondition  
 Deepen  Abandon  Other

4. PROPOSED USE  
 Domestic  Irrigation  Test  
 Municipal/Industrial  Monitor  Stock

5. WELL TYPE  
 Cable  Rotary  RVC  
 Air  Other

6. LITHOLOGIC LOG

| Material                         | Water Strata | From | To  | Thick-ness |
|----------------------------------|--------------|------|-----|------------|
| SOFT BLACK VOLCANIC ROCK         |              | 0    | 25  | 25         |
| MED. HARD BLACK VOLCANIC ROCK    |              | 25   | 167 | 142        |
| FRACTURED BLACK VOLCANIC ROCK    | X            | 167  | 170 | 3          |
| HARD BLACK VOLCANIC ROCK         |              | 170  | 230 | 60         |
| FRACTURED BLACK VOLCANIC ROCK    | X            | 230  | 237 | 7          |
| HARD BLACK VOLCANIC ROCK         | X            | 237  |     |            |
| WITH OCCASIONAL SMALL FRACTURING |              |      | 530 | 293        |

8. WELL CONSTRUCTION  
 Depth Drilled 530 Feet Depth Cased 530 Feet

HOLE DIAMETER (BIT SIZE)  
 From 0 To 60  
31 Inches 60 Feet  
17 1/2 Inches 530 Feet

CASING SCHEDULE

| Size O.D. (Inches) | Weight/Ft. (Pounds) | Wall Thickness (Inches) | From (Feet) | To (Feet) |
|--------------------|---------------------|-------------------------|-------------|-----------|
| 20                 | 53                  | .250                    | 0           | 60        |
| 12 3/4             | 33                  | .250                    | +2          | 188       |
| 12 3/4             | 33                  | .250                    | 522         | 530       |

Perforations:  
 Type perforation MILL SLOT & SCREEN  
 Size perforation .080  
 From 188 feet to 522 feet

Surface Seal:  Yes  No Seal Type:  
 Depth of Seal 50 FT.  Neat Cement  
 Placement Method:  Pumped  Cement Grout  
 Poured  Concrete Grout

Gravel Packed:  Yes  No  
 From 50 feet to 530 feet

9. WATER LEVEL  
 Static water level 74 feet below land surface  
 Artesian flow N/A G.P.M. N/A P.S.I.  
 Water temperature °F Quality °F

10. DRILLER'S CERTIFICATION  
 This well was drilled under my supervision and the report is true to the best of my knowledge.

Name LANG EXPLORATORY DRILLING  
 Address 2286 WEST 1500 SOUTH  
SALT LAKE CITY, UT 84104

Nevada contractor's license number 0021976  
 issued by the State Contractor's Board.

Nevada driller's license number issued by the  
 Division of Water Resources, the on-site driller 1388

Signed Gene Nagel  
 By driller performing actual drilling on site or contractor

Date DECEMBER 31, 1991

Date started DECEMBER 9, 1991  
 Date completed DECEMBER 20, 1991

7. WELL TEST DATA

| TEST METHOD:   | G.P.M. | Draw Down (Feet Below Static) | Time (Hours) |
|--|--------|-------------------------------|--------------|
| <input type="checkbox"/> Bailer <input checked="" type="checkbox"/> Pump <input type="checkbox"/> Air Lift | 500    | 154                           | 48           |

92 JAN 14 AM 1:39  
STATE ENGINEER