



PRINT OR TYPE ONLY
 DO NOT WRITE ON BACK

WELL DRILLER'S REPORT

Please complete this form in its entirety in accordance with NRS 534.170 and NAC 534.340

NOTICE OF INTENT NO. 18731

1. OWNER Goldfields Operating Co. ADDRESS AT WELL LOCATION Below future events ponds, Leach pad at Chimney Creek Mine Golconda, Nevada
 MAILING ADDRESS P.O. BOX 69 Golconda, Nevada 89414
 2. LOCATION SE 1/4 NE 1/4 Sec. 17 T 39 X N/S R. 43 E Humboldt County
 PERMIT NO. M/O - 473 Issued by Water Resources Parcel No. Subdivision Name

3. WORK PERFORMED
 New Well Replace Recondition Domestic Irrigation Test Cable Rotary RVC
 Deepen Abandon Other..... Municipal/Industrial Monitor Stock Air Other.....

6. LITHOLOGIC LOG

Material	Water Strata	From	To	Thick-ness
Sandy Clay		0	26	26
70% Clay/ Caleachy Stringers		26	120	94
70% Clay/ Cobbles Sand Stringers		120	145	25
70% Clay/ Boulders inbeded Clay Stringers		145	241	96
50% Clay/ Boulders inbeded with Clay		241	271	30
Sand and Gravel/ 20% Clay	X	271	286	15
70% Clay/Gravel Stringers		286	300	14

8. WELL CONSTRUCTION
 Depth Drilled 300 Feet Depth Cased 300 Feet
 HOLE DIAMETER (BIT SIZE)
 From To
9 7/8 Inches 18 Feet 300 Feet
18 Inches 0 Feet 18 Feet
 Inches Feet Feet

CASING SCHEDULE

Size O.D. (Inches)	Weight/Ft. (Pounds)	Wall Thickness (Inches)	From (Feet)	To (Feet)
4" PVC	-	Sch. 40	+3	300
12"	-	.188	0'	18'

Perforations:
 Type perforation Sch. 40
 Size perforation 0.020 Screen
 From 200 feet to 300 feet
 From..... feet to..... feet
 From..... feet to..... feet
 From..... feet to..... feet
 From..... feet to..... feet

Surface Seal: Yes No Seal Type:
 Depth of Seal 190 Neat Cement
 Placement Method: Pumped Cement Grout
 Poured Concrete Grout
 Gravel Packed: Yes No Silica Sand
 From 190 feet to 300 feet

9. WATER LEVEL
 Static water level 155 feet below land surface
 Artesian flow - G.P.M. - P.S.I.
 Water temperature cold °F Quality good

10. DRILLER'S CERTIFICATION
 This well was drilled under my supervision and the report is true to the best of my knowledge.
 Name Humboldt Drilling and Pump Co. Contractor
 Address P.O. BOX 590 Winnemucca, Nevada 89446-0590 Contractor

Nevada contractor's license number issued by the State Contractor's Board 015234
 Nevada driller's license number issued by the Division of Water Resources, the on-site driller 1448
 Signed [Signature] By driller performing actual drilling on site or contractor
 Date 1-6-92

Date started 12-18, 1991
 Date completed 12-27, 1991

7. WELL TEST DATA

TEST METHOD: <input type="checkbox"/> Bailor <input type="checkbox"/> Pump <input checked="" type="checkbox"/> Air Lift			
G.P.M.	Draw Down (Feet Below Static)	Time (Hours)	
<u>5</u>	<u>air on rig</u>	<u>6 hrs.</u>	

92 JAN -8 NO 37
 STATE ENGINEERS OFFICE